

## MSTBC-MT 0,5-1,0 BA

Order No.: 3190645

Supplied in tape form - please note the drawing.

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3190645>

Module female contact, is inserted into the MSTBC connector shell after the conductor has been crimped, for conductors from 0.5 - 1.0 mm<sup>2</sup>, ribbon contact

### Commercial data

GTIN (EAN)	4017918117436
sales group	E192
Pack	4000 pcs.
Customs tariff	85366990
Weight/Piece	0.00069 KG
Catalog page information	Page 497 (CC-2009)

### Product notes

WEEE/RoHS-compliant since:  
01/01/2003

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Technical data

Nominal current	12 A (with 1 mm <sup>2</sup> conductor cross section)
Conductor cross section stranded min.	0.5 mm <sup>2</sup>
Max. conductor cross section, stranded	1 mm <sup>2</sup>

**Connection data**


Core diameter including insulation	1.4 mm ... 2.31 mm
Stripping length of individual wires	3.5 mm

**Material data**

Contact material	CuFe
Contact surface material	Tin-plated

**Diagrams/Drawings**

Dimensioned drawing



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;