

[Skip to content](#)

[Corporate Home](#) | [Electronic Components](#) | [Segments](#) | [Who We Are](#)

Worldwide



Our commitment. Your advantage.

Search

By:



[Sign In](#) | [Register \(Why Register?\)](#)

[Products](#)

- Connectors
- Electromechanical Components
- Electronic Modules
- Fiber Optics
- Filters
- Identification Labeling Products
- Passive Components
- Power Sources
- RF & Microwave Products
- Tooling Products
- Touch Screen Displays
- Tubing, Molded and Harnessing Products
- Wire, Cable and Cable Assemblies
- List all Product Types

- Aerospace & Defense
- Appliance
- Automotive
- Communications
- Computer & Consumer Electronics
- Industrial & Commercial
- Instrumentation & Medical Equipment
- By Brand
- A to Z
- [Documentation](#)
 - Find
 - Documents & Drawings
 - Find CAD Models
 - SPICE/Electrical Models
 - NAFTA Certificate of Origin
 - White Papers
- [Resources](#)
 - RoHS
 - Compliance & Alternates
 - Cross Reference Products
 - Compare Multiple Products
 - Check Distributor Inventory
 - Find Authorized Distributors
- [My Account](#)
 - Sign In
 - Register
- [Customer Support](#)
 - Support
 - RoHS Support Center
 - Glossary of Terms
 - eBulletin Newsletter

[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > Product Details

LR4-730F Product Details



LR4-730F

Raychem Part Number: A93367-000

 [Active](#)

PolySwitch Resettable Devices

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Strap Battery Application
- Family Name = LR4
- Weldable Strap Construction
- IH (Room Temperature) = 7.3 Amps.
- IT (Room Temperature) = 14.10 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [LR4-730F](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 7.3
- [IT \(Room Temperature\) \(Amps.\)](#) = 14.10
- [Vmax Operating \(V\)](#) = 20
- [Rmin \(\)](#) = 0.006
- [Rmax \(\)](#) = 0.012
- [R1 Max \[Post Trip\] \(\)](#) = 0.015
- [UL Rated Current \(Amps.\)](#) = 100
- Tripped Power Dissipation (Typical) (W) = 3.30

Termination Related Features:

- Construction = Weldable Strap

Body Related Features:

- CSA File No. = 78165C

Contact Related Features:

- [Family Name](#) = LR4

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Strap Battery

Packaging Related Features:

- Packaging Method = Bulk

Other:

- Brand = Raychem

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved