

TF 2-2-VA-230AC

This item is no longer available. Should you have any questions, please contact our Sales Team.

Order No.: 2858027

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2858027>

Protective plug TF with varistors between 2 signal lines and earth, temperature-monitored with disconnect device, ground connection line. Nominal voltage: 230 V AC

Commercial data	
GTIN (EAN)	4017918829568
Note	Made-to-order
sales group	J240
Pack	10 pcs.
Customs tariff	85363010
Weight/Piece	0.0439 KG

Product notes

WEEE/RoHS-compliant since:
06/07/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
General	
Housing material	PA
Inflammability class acc. to UL 94	V2
Ambient temperature (operation)	-40 °C ... 80 °C
Degree of protection	IP20
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 2.20

Protective circuit

Nominal voltage U_N	230 V
Arrester rated voltage U_C (Core-Earth)	250 V AC
Nominal current I_N	3 A (75°C)
Operating effective current I_C at U_C	$\leq 10 \mu\text{A}$
Nominal discharge surge current I_n (8/20) μs (Core-Core)	1 kA
Nominal discharge surge current I_n (8/20) μs (Core-Earth)	1 kA
Max. discharge surge current I_{max} (8/20) μs maximum (Core-Core)	4.5 kA
Max. discharge surge current I_{max} (8/20) μs maximum (Core-Earth)	4.5 kA
Response time t_A (Core-Core)	$\leq 25 \text{ ns}$
Response time t_A (Core-Earth)	$\leq 25 \text{ ns}$
Max. required back-up fuse	3 A

Certificates / Approvals



Certification

GOST

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;