


### SL Series Multimedia Jacks




Description	Figure	Part Number	
RCA	A	Red Dielectric	1479230-X
		White Dielectric	1479231-X
		Yellow Dielectric	1479232-X
S-Video	B	1375149-X	

X denotes color: -1 = Almond, -2 = Black, -3 = White, -4 = Gray, 1--1 = Electrical Ivory


### Product Facts

- :: For use where distances are less than 130 ft.
- :: Uses Standard 110 Termination and will accept 26-22 AWG conductors
- :: RCA Multimedia Jack
  - ... For audio and video signals
  - ... Uses one pair of twisted-pair cable
  - ... White, red or yellow dielectrics to match home theater equipment
- :: S-Video Multimedia Jack
  - ... For S-Video Y/C (Luminance/Chrominance Black and White/Color) signals
  - ... Uses two pairs of a standard twisted-pair cable

### SVGA Assembly PART NUMBER 1479287-2



WIRING DIAGRAM



### Product Facts

- :: Works with VGA and SVGA signals
- :: Features 110-Style termination for easy installation
- :: Is suitable for use with standard Category 5e or 6 UTP or FTP (recommended) cables
- :: Can be used where distances between monitor and computer do not exceed:
  - ... 15 ft. with Cat 5e UTP cable
  - ... 20 ft. with Cat 6 UTP cable
  - ... 35 ft. with Cat 5e or 6 FTP cables
- :: Requires a 9th conductor and is recommended for use with FTP cables (utilizes drain wire for 9th conductor)
- :: Dimensions:
  - 1.180" D x 1.480" W x 0.875" H
- :: Stuffer caps and hex head stand-off screws included