54

3.2



# **TWISTED PAIR PRODUCTS**

## **SL Series Multimedia Modules**


### **SL Series Multimedia Modules**











WIRING DIAGRAM

TERMINAL.	HÐ	
BLECK	15 P3	
Α	1	
В	5	
С	3	
0	4,5	
E	GN	
F	6	
G	7	
H	8	
I	13	
J	14	
	BLOCK B C D	

SIGNAL
REB INPUT
BRUE INPUT
BRUE INPUT
BRUE INPUT
GND HORIZ/VERT.SYNC
OF GND RED
GND GREEN
GND GREEN
GND BRUE
HURIZ SYNC
VERT SYNC

### **Product Facts**

- :: Fit SL Series Faceplates
- :: Front loading
- :: Optical Fiber Coupler Modules are suitable for use with single-mode or multimode connectors as listed
- :: SVGA Multimedia Modules:
  - Available loaded with a SVGA 110
     Termination Module or unloaded for use with a SVGA coupler (sold separately)
- :: SVGA 110 Termination Module
  - ··· Works with VGA and SVGA signals
  - Features 110-Style termination for easy installation
  - Is suitable for use with standard Category 5e or 6 UTP or FTP (recommended) cables
  - Can be used where distances between monitor and computer do not exceed:
    - 15 ft with Cat 5e UTP cable
    - 20 ft with Cat 6 UTP cable
    - 35 ft with Cat 5e or 6 FTP cables
  - Requires a 9th conductor and is recommended for use with FTP cables (utilizes drain wire for 9th conductor)

Description			Units	Figure	Part Number
2-Fiber Coupler	Duplex SC	Single-mode	1	_	1375306-X
		Multimode	1	А	1375123-X
	Duplex SC to ST	Multimode	1	В	1375241-X
SVGA	Loaded		1	С	1479288-X
	Unloaded		1	D	1479079-X

X denotes color: -1 = Almond, -2 = Black, -3 = White, -4 = Gray, 1--1 = Electrical Ivory

For more information, call 1-800-553-0938