



KEYING OPTIONS
 SOME DETAIL OMITTED FOR CLARITY

△ HOUSING: NYLON MOLDING COMPOUND, BLACK.
 TERMINALS: 0.3(.012) THICK PHOS BRONZE.
 PLATING: NICKEL UNDERPLATE OVER ENTIRE TERMINAL. 2.54µm(.000100) MINIMUM THICKNESS.
 LOCALIZED PLATING AREA: 0.254µm(.000100) THICK GOLD OVER 1.016µm(.000400) MINIMUM THICK PALLADIUM NICKEL (OVER 0.051µm(.000002) MINIMUM THICK GOLD WHEN REQUIRED BY PROCESS CONDITIONS).

2. 558666-1 KEY1 (CLOSED) AS SHOWN.

KEY	PART NUMBER
KEY 5	558666-5
KEY 4	558666-4
KEY 3	558666-3
KEY 2	558666-2
KEY 1	558666-1
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 10/31/90	BY: [Signature]	REV: 23
DRAWING: 558666-5		DATE: 10/31/90	BY: [Signature]	REV: 23
MATERIAL: [Symbol]		DATE: 10/31/90	BY: [Signature]	REV: 23
PREP: [Symbol]		DATE: 10/31/90	BY: [Signature]	REV: 23
CHECK: [Symbol]		DATE: 10/31/90	BY: [Signature]	REV: 23
APPROVE: [Symbol]		DATE: 10/31/90	BY: [Signature]	REV: 23
CUSTOMER DRAWING		DATE: 10/31/90	BY: [Signature]	REV: 23

AMP Incorporated
 Harrisburg, PA 17105-3608

CONNECTOR ASSEMBLY,
 CABLE, 15 POSITION, INFOPORT,
 SERIES III

AMP 00778-0-558666