

| Contact Size | RG/U Cable | Contact Part No. | | "O" Crimp Tooling | | | Military Hex Crimp Tooling | | | | Compression Crimp Tooling | | | |
|-----------------------------------|----------------------------|------------------|-----------------------|-------------------|------------|--------------------|----------------------------|---------|-----------------|---------------|---------------------------|-----------------|------------------|-------------------|
| | | | | Center Contact | | | Center Contact | | Ferrule | | | | | |
| | | | | Pin | Socket | Tool (M22520/) | Positioner/ Die | Ferrule | Tool (M22520/) | Die (M22520/) | Tool (M22520/) | Die (M22520/) | Tool (M22520/) | Locator (M22520/) |
| O Crimp | | | | | | | | | | | | | | |
| 1 | 402 Semi-Rigid .141 [3.58] | 225837-1 | — | 601966-1 (2-01) | 1-601966-9 | 91905-1' or 91904' | — | — | — | — | — | — | — | |
| | 402 Semi-Rigid .141 [3.58] | 222018-1 | — | — | — | — | — | — | — | — | — | 59980-1 (36-01) | 220220-2 (36-06) | 312253-1 (36-03) |
| | 405 Semi-Rigid .086 [2.18] | 222018-2 | — | — | — | — | — | — | — | — | — | 59980-1 (36-01) | 220220-2 (36-06) | 312253-2 (36-02) |
| | 214 | — | 225831-1 211229-1* | 220015-1 | — | 220015-1 | — | — | — | — | — | — | — | — |
| | 142, 142A, 142B | — | 225831-3 446709-1* | 91902-1' | — | 91902-1' | — | — | — | — | — | — | — | — |
| | 393 | — | 225831-6 446709-3* | 220015-1 | — | 220015-1 | — | — | — | — | — | — | — | — |
| Military Hex Crimp | | | | | | | | | | | | | | |
| 1 | 214 | 447095-1 | 447087-1 | — | — | — | 608650-1 (5-01) | (5-25) | 608650-1 (5-01) | (5-25) | — | — | — | |
| | 213 | 447095-2 | 447087-2 446709-5* | — | — | — | 608650-1 (5-01) | (5-25) | 608650-1 (5-01) | (5-25) | — | — | — | |
| | 142, 142A, 142B | 447095-3 | 447087-3 446709-6* | — | — | — | 608650-1 (5-01) | (5-11) | 608650-1 (5-01) | (5-11) | — | — | — | |
| | 393 | 447095-4 | 447087-4 446709-7* | — | — | — | 608650-1 (5-01) | (5-25) | 608650-1 (5-01) | (5-25) | — | — | — | |
| | ECS 311201 | — | 447087-5 446709-2* | — | — | — | 608650-1 (5-01) | (5-29) | 608650-1 (5-01) | (5-29) | — | — | — | |
| | 214 | — | 446549-3* | — | — | — | M22520/5-01** | — | — | M22520/5-25 | — | — | M22520/5-25 | |
| Modified 1 Straight Exit | 142 | — | 446549-1 | — | — | — | M22520/5-01** | — | — | M22520/5-11 | — | — | M22520/5-11 | |
| | 393 | — | 446549-5* | — | — | — | M22520/5-01** | — | — | M22520/5-25 | — | — | M22520/5-25 | |
| | Times AA5886 | — | 446549-6* | — | — | — | M22520/5-01** | — | — | M22520/5-25 | — | — | M22520/5-04 | |
| | Times AA5887 | — | 446549-2* | — | — | — | M22520/5-01** | — | — | M22520/5-29 | — | — | M22520/5-29 | |
| | ESC 311201 | — | 446549-4* | — | — | — | M22520/5-01** | — | — | M22520/5-29 | — | — | M22520/5-29 | |
| | SMA ADAPTER | 446748-1 | — | — | — | — | — | — | — | — | — | — | — | |

*Socket with mounting hardware. Mounting hardware for Size 1 Straight Exit Contacts includes: backup plate, spring, retaining ring, O-ring, washers and screws.
 **Tyco Electronics does not sell Hand Tool M22520/5-01. However, it can be purchased from: Daniels Manufacturing Corp, 6103 Anno Ave., Orlando, FL 32809, 800-327-2432.

- Notes:**
1. SDE die used with hand tool frame 354940-1.
 2. Hardware kit for Size 1 COAXICON Socket Contacts (used on 71C1 or C2 inserts) includes all mounting hardware required (retention plate, washers, O-ring, spring, screws and retention clip). Kit Number 447118-1.
 3. Size 1 Coaxicon Pin Contacts require retention plate 211217-2 and four screws 211558-1.