



### Dimensions (In.)



### ■ SPECIFICATIONS

- Impedance variation:  $\pm 10\%$  @ 1KHz
- DC Resistance tolerance:  $\pm 15\%$
- Insulation:  $>10M\Omega$  @ 100VDC
- Core type / size: EI-14
- Breakdown voltage: 100VAC Hipot for 1 minute
- Waxing: Vacuum treatment can be water washed with water temperature less than  $20^{\circ}C$
- Max output: 75mW
- Freq. response:  $\pm 3dB$ , 300Hz-3.5 KHz @ 1KHZ 0dB
- Can be water washed with water temperature less than  $20^{\circ}C$

Mouser Stock No.	Impedance		Resistance	
	PRI	SEC	PRI	SEC
42XL001	500 $\Omega$	8 $\Omega$	35 $\Omega$	1 $\Omega$
42XL002	10K $\Omega$	2K $\Omega$	580 $\Omega$	200 $\Omega$
42XL003	1.2K $\Omega$	8 $\Omega$	80 $\Omega$	1 $\Omega$
42XL009	500 $\Omega$	500 $\Omega$	40 $\Omega$	38 $\Omega$
42XL016	600 $\Omega$	600 $\Omega$	65 $\Omega$	55 $\Omega$
42XL031	600 $\Omega$	100 $\Omega$	74 $\Omega$	28 $\Omega$