



Low Profile, Small Case Size Engineering Kit #11

| Part Number | Case Size | Cap μ F | Voltage | DCL V_R | DF 120Hz | ESR 100kHz Ω |
|------------------------------------|-----------|-------------|---------|--------------|----------|---------------------|
| T491A107M004AT | A/3216-18 | 100.0 | 4 | 4.0 μ A | 30% | 4.0 |
| T494R106M006AT | R/2012-12 | 10.0 | 6.3 | 0.6 μ A | 8% | 6.0 |
| T494R475M010AT | R/2012-12 | 4.7 | 10 | 0.5 μ A | 8% | 8.0 |
| T494T226M010AT | T/3528-12 | 22.0 | 10 | 2.2 μ A | 12% | 6.0 |
| T494A156M010AT | A/3216-18 | 15.0 | 10 | 1.5 μ A | 8% | 4.0 |
| T494U686M010AT | U/6032-15 | 68.0 | 10 | 6.8 μ A | 10% | 1.2 |
| T494R225M016AT | R/2012-12 | 2.2 | 16 | 0.5 μ A | 8% | 20.0 |
| T494U336M016AT | U/6032-15 | 33.0 | 16 | 5.3 μ A | 12% | 2.2 |
| T491R105M020AT | R/2012-12 | 1.0 | 20 | 0.5 μ A | 6% | 20.0 |
| T494S155M020AT | S/3216-12 | 1.5 | 20 | 0.5 μ A | 6% | 9.0 |
| T494T335M020AT | T/3528-12 | 3.3 | 20 | 0.7 μ A | 6% | 4.0 |
| T494U106M020AT | U/6032-15 | 10.0 | 20 | 2.0 μ A | 6% | 0.8 |
| T520T476M006ATE070 | T/3528-12 | 47.0 | 6.3 | 30.0 μ A | 8% | 70.0 |
| T520M157M006ATE200 | M/3528-15 | 150.0 | 6.3 | 95.0 μ A | 8% | 200.0 |
| T520U107M006ATE055 | U/6032-15 | 100.0 | 6.3 | 63.0 μ A | 8% | 55.0 |
| T520W227M004ATE040 | W/7343-15 | 220.0 | 4 | 88.0 μ A | 10% | 40.0 |
| T528I476M006ATE150 | I/3216-10 | 47.0 | 6.3 | 29.6 μ A | 10% | 150.0 |
| T528I336M010ATE150 | I/3216-10 | 33.0 | 10 | 33.0 μ A | 10% | 150.0 |