



Alle Rechte vorbehalten / All rights reserved

5 4 3 2 1



Bestell-Nummer / Part No.		D	Leiterquerschnitt wire gauge		Abisolierlänge der Litze stripping length
versilbert silver plated	vergoldet gold plated		mm <sup>2</sup>	AWG	
09 15 000 6204	09 15 000 6224	0,90	0,14-0,37	26-22	8
09 15 000 6203	09 15 000 6223	1,10	0,5	20	
09 15 000 6205	09 15 000 6225	1,30	0,75	18	
09 15 000 6202	09 15 000 6222	1,45	1	18	
09 15 000 6201	09 15 000 6221	1,75	1,5	16	
09 15 000 6206	09 15 000 6226	2,25	2,5	14	
09 15 000 6207		0,90	0,14-0,37	26-22	

1) Nur für Buchanan Crimpwerkzeug Einstell $\phi$  1,0/  
only for Buchanan crimping tool adjusting  $\phi 0,1$



All Dimensions in mm  
Original Size DIN A 4

Techn. Character.

Nicht tolerierte Masse / free size tolerances

	Dat.	Name	Masstab/Scale
Detail.	22.03.99	Kö	2:1
Insp.		SDT	
Stand.			

**Han D / R15 Buchsenkontakt**  
Crimpkontakt gedreht 10A  
crimpcontact twisted 10A

410609	15.07.03	DY
25592		
Mod.	Dat.	Name

HARTING Electric GmbH & Co. KG  
D-32339 Espelkamp



**TB 09 15 000 62..**  
Sub.

Blatt / page