

TRF250 - 120T - RF-B-0.5 - 2 Product Details



TRF250 - 120T - RF-B-0.5 - 2

 [Active](#)

PolySwitch Resettable Devices

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Telecom Application
- ? Family Name = TR250
- ? Through Hole Construction
- ? IH (Room Temperature) = .12 Amps.
- ? IT (Room Temperature) = .24 Amps.

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? UL Recognized = File No. E74889
- ? Comment = Devices are available with 0.5 ohm resistance matching.; Designed for equipment needing to meet ITU K.20, K.21, K.45 recommendations.

Electrical Characteristics:

- ? [IH \(Room Temperature\) \(Amps.\)](#) = 0.12
- ? [IT \(Room Temperature\) \(Amps.\)](#) = 0.24
- ? [Vmax Operating \(V\)](#) = 60
- ? [Rmin \(?\)](#) = 6.00
- ? [Rmax \(?\)](#) = 10.500
- ? [R1 Max \[Post Trip\] \(?\)](#) = 16.00
- ? [Vmax Interrupt \(V rms\)](#) = 250
- ? [UL Rated Current \(Amps.\)](#) = 3
- ? Tripped Power Dissipation (Typical) (W) = 1.00
- ? R (Typical) (?) = 8.25
- ? Resistance Matching (?) = 0.5
- ? UL Rated Voltage (V) = 60

Termination Related Features:

- ? Construction = Through Hole

Body Related Features:

- ? Lead Type = Kinked
- ? CSA File No. = 78165C

Contact Related Features:

- ? Family Name = TR250

Configuration Related Features:

- ? Coating = Coated

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant
- ? TUV Certificate No. = R72041425

Conditions for Usage:

- ? [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- ? Application = Telecom

Packaging Related Features:

- ? Packaging Method = Tape & Reel

Other:

- ? Brand = Raychem