

TR250-120UT Product Details



TR250-120UT

TE Part Number: 455540-000

 **Obsolete**

[Add to Part List](#)
[Contact Product Information Center](#)

PolySwitch Resettable Devices

 [Always ELV Compliant \(Find RoHS Compliant Alternates/Statement of Compliance\)](#)

Product Highlights:

- Telecom Application
- Family Name = TR250
- Through Hole Construction
- IH (Room Temperature) = .12 Amps.
- IT (Room Temperature) = .24 Amps.

[View all Features](#) | [Find Similar Products](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889
- CSA File No. = 78165C
- Comment = Devices are available with 0.5 ohm resistance matching.; Designed for equipment needing to meet ITU K.20, K.21, K.45 recommendations.

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 0.12
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.24
- [Vmax Operating \(V\)](#) = 60
- [Rmin \(Ω\)](#) = 7.00
- [Rmax \(Ω\)](#) = 12.000
- [R1 Max \[Post Trip\] \(Ω\)](#) = 16.00
- [Vmax Interrupt \(V rms\)](#) = 250
- [UL Rated Current \(Amps.\)](#) = 3
- Tripped Power Dissipation (Typical) (W) = 1.00
- R (Typical) (Ω) = 9.50
- UL Rated Voltage (V) = 60

Termination Related Features:

- Construction = Through Hole

Body Related Features:

- Lead Type = Kinked

Contact Related Features:

- Family Name = TR250

Configuration Related Features:

- Coating = Uncoated

Industry Standards:

- [RoHS/ELV Compliance](#) = ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was ELV compliant
- TUV Certificate No. = R72041425

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Telecom

Packaging Related Features:

- Packaging Method = Bulk, Tape & Reel

Other:

- Brand = Raychem