Customer Support

Products Documentation Resources My Account Home > Products > Switches > Product Feature Selector > Product Details

## 1825027-5 Product Details



▶ Check Pricing & Availability

Search for Tooling Product Feature Selector Contact Us About This Product

Quick Links

**Pushbutton Switches** 

Always EU RoHS/ELV Compliant (Statement of Compliance)

### **Product Highlights:**

- Switch Mechanical
- Tactile
- Single Pole Single Throw Configuration (Pole-Throw)
   Contact Rating = 50mA
   Operating Function = Off [On]

View all Features TE Internal Number: 1825027-5



1825027-5







Additional Information:

### Related Products:

🔁 <u>View 3D PDF</u> **Documentation & Additional Information** 

Product Drawings:
• MICRO-MINIATURE PUSHBUTTON SWITCH (PDF, English)

## Catalog Pages/Data Sheets:

### Product Specifications:

## Application Specifications:

### Instruction Sheets:

# CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version G1) • 3D Model (IGES, Version G1)

- 3D Model (STEP, Version G1)

List all Documents

## Product Features (Please use the Product Drawing for all design activity)

- Product Type Features:
   Product Type = Switch Mechanical
  - Tactile = Yes
  - Configuration (Pole-Throw) = Single Pole Single Throw
  - Mount Angle = Right Angle
  - Termination Type = Printed Circuit
  - Actuator Style = Round
  - Comment = (On) indicates momentary position.

## Electrical Characteristics: • Contact Rating = 50mA

## Body Related Features: • Series = FSMRAJ

- Mount Style = Through-Hole
- Actuator Length (mm [in]) = 1.24 [0.049]
- Actuator Profile = Extended
- Actuator Color = Black
- Case Material = PBT
- Actuator Material = PBT

## **Contact Related Features:**

- Contact Base Material = Copper Alloy

## Housing Related Features:

- Process Sealed = No
- Low Profile = No

## Configuration Related Features: • Operating Function = Off [On]

- Ganged = No
- ESD Grounding Terminal = Without
- Actuator Force (g [oz]) = 160.00 [5.648]
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = With
- Snap Action = Without • Tactile Feel = With
- Switch Height (mm [in]) = 7.00 [0.276]

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:
• Temperature Rating = Standard

## Packaging Related Features: • Packaging Method = Loose Piece

Other:

• Brand = Tyco Electronics



Corporate Information Who We Are

Investors

Careers

News Room

Supplier Portal

**Ouick Links** 

Check Distributor Inventory

Cross Reference

Find Documents & Drawings Product Compliance Support Center

Site Map

**Customer Support** 

Email or Chat with Us Find a Phone Number

Search Knowledge Base Manage Your Account

Sign up for our eNewsletter











© 2010 Tyco Electronics All Rights Reserved | Privacy Policy