Our commitment. Your advantage

My Account

Home > Products > By Type > Switches > Product Feature Selector > Product Details

#### 1-1825098 -2 Product Details



1-1825098 -2

Add to Part List

#### **Pushbutton Switches**

Always EU RoHS/ELV Compliant (Statement of Compliance)

**Customer Support** 

#### **Product Highlights:**

- ? Switch Mechanical
- Not Tactile
- Single Pole Double Throw
   Configuration (Pole Throw)
   Contact Rating = 20V
- ? Operating Function = Momentary

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u>



#### **Quick Links**

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector

Contact Us About
This Product

#### **Documentation & Additional Information**

### **Product Drawings:**

PUSHBUTTON SWITCH, TPC SERIES (PDF, English)

#### Catalog Pages/Data Sheets:

? None Available

### **Product Specifications:**

? None Available

### **Application Specifications:**

? None Available

#### Instruction Sheets:

? None Available

#### **CAD Files:**

? None Available

#### Additional Information:

Product Line Information

#### Related Products:

? Tooling

List all Documents

#### **Product Features**

(Please use the Product Drawing for all design activity)

# **Product Type Features:**

- Product Type = Switch Mechanical
- ? Tactile = No
- Configuration (Pole -Throw) = Single Pole Double Throw
- ? Mount Angle = Vertical
- ? Termination Type = Wire Lugs
- ? Actuator Style = Round

#### **Electrical Characteristics:**

? Contact Rating = 20V

### **Body Related Features:**

- ? Series = TP
- ? Mount Style = Panel
- ? Actuator Length (mm [in]) = 3.48 [0.137]
- ? Actuator Profile = Extended
- ? Actuator Color = Black
- ? Bushing Diameter = 10/48
- ? Case Material = Polyester
- ? Actuator Material = Polyamide

#### **Contact Related Features:**

? Contact Plating = Silver

### **Housing Related Features:**

- Process Sealed = No
- ? Low Profile = No
- ? Bushing Style = Threaded

# Configuration Related Features:

- Operating Function = Momentary
- ? Ganged = No
- <sup>?</sup> ESD Grounding Terminal = Without
- Actuator Force (g [oz]) = 50.00 400.00 [1.770 14.120]
- ? Number of Actuators = Single
- ? Illuminated = No
- ? Dust Proof = No
- ? Support Bracket = Without
- ? Snap Action = Without

### Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

## Conditions for Usage:

7 Temperature Rating = High

## **Packaging Related Features:**

? Packaging Method = Loose Piece

#### Other:

? Brand = Alcoswitch

Provide Website Feedback | Need Help?