Search

₹ Tyco Electronics Our commitment. Your advantage. Products Documentation Resources My Account Customer Support <u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Switches</u> > <u>Product Feature Selector</u> > Product Details

**D** 

44	Slide Switches		Quick Links	
1825115-1 (SLS121PC04) ✓ Active	Always EU RoHS/ELV Compliant (Statement of Compliance)  Product Highlights:  Number of Positions = 2 Single Pole - Double Throw Configuration (Pole-Throw) Actuator Style = Top Actuator Color = Black SLS-PC Series View all Features		Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product	
Documentation & Add	ditional Information			
Product Drawings: • <u>SLIDE SWITCH, SPDT (SLS121PC &amp; SLS121PCG)</u> (PDF, En			<ul> <li>Additional Information:</li> <li>Product Line Information</li> </ul>	
Catalog Pages/Data • None Available	Sheets:	Related Pr • <u>Toolin</u>		
<ul><li>Product Specification</li><li>None Available</li></ul>	s:			
Application Specificat <ul> <li>None Available</li> </ul> <li>Instruction Sheets: <ul> <li>None Available</li> </ul> </li> <li>CAD Files: <ul> <li>None Available</li> </ul> </li>	ions:			
	Li	st all Documents		
Product Features (Plea	ase use the Product Drawing for all design act	ivity)		
<ul> <li>Product Type Features:</li> <li>Number of Positions = 2</li> <li>Configuration (Pole-Throw) = Single Pole - Double Throw</li> <li>Actuator Style = Top</li> <li>Mount Angle = Vertical</li> <li>Grade = Economy</li> <li>Termination Type = PC</li> </ul>		Contact Related Features: • Contact Plating = Silver • Contact Material = Copper Alloy Configuration Related Features: • Terminal Configuration = Standard • Number of Actuators = Single		
<ul> <li>Fermination Type = FC</li> <li>Electrical Characteristics: <ul> <li>Contact Rating = 150mA @ 12 VDC, 250mA @ 125 VAC</li> </ul> </li> <li>Body Related Features: <ul> <li>Actuator Color = Black</li> <li>Series = SLS-PC</li> <li>Mount Style = Through-Hole</li> <li>PCB Tail Length (mm [in]) = 4.32 [0.170]</li> <li>Actuator Length (mm [in]) = 5.00 [0.197]</li> <li>Actuator Material = Polycarbonate</li> </ul> </li> </ul>		<ul> <li>Industry Standards:         <ul> <li>RoHS/ELV Compliance = RoHS compliant, ELV compliant</li> <li>Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>RoHS/ELV Compliance History = Always was RoHS compliant</li> </ul> </li> <li>Identification Marking:         <ul> <li>Stamped Marking = With</li> </ul> </li> <li>Other:             <ul> <li>Brand = Tyco Electronics</li> </ul> </li> </ul>		

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support © 2007 Tyco Electronics Corporation All Rights Reserved