


6-1825011 -4 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



6-1825011 -4
(ASF62RG04)
 [Active](#)

Slide Switches

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Number of Positions = 2
- ? Six Pole - Double Throw Configuration (Pole -Throw)
- ? Actuator Style = Flush, Side
- ? Actuator Color = White
- ? ASE/F Series

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [SLIDE SWITCH ASF, AUTO -INSERTABLE, THRU -HOLE AND SUR...](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Number of Positions](#) = 2
- ? Configuration (Pole -Throw) = Six Pole - Double Throw
- ? Actuator Style = Flush, Side
- ? Mount Angle = Right Angle
- ? Grade = Telecom
- ? Termination Type = PC
- ? Comment = Open Ended (Unsealed) Case

Electrical Characteristics:

- ? Contact Rating = 0.4VA

Body Related Features:

- ? Actuator Color = White
- ? Series = ASE/F
- ? Mount Style = Through -Hole
- ? Switch Style = Auto -insertable
- ? PCB Tail Length (mm [in]) = 4.06 [0.160]
- ? Actuator Material = Polyester

Contact Related Features:

- ? Contact Plating = Gold
- ? Contact Material = Copper Alloy

Configuration Related Features:

- ? Terminal Configuration = Standard
- ? Number of Actuators = Single

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Identification Marking:

- ? Stamped Marking = With

Other:

- ? Brand = Tyco Electronics