



Search by Keyword or Part #

1825117-1 Product Details

Have a Question?

Chat with a Product Information Specialist



1825117-1

TE Internal Number: 1825117-1

 [Active](#)

Slide Switches

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- 3 Positions
- Single Pole - Three Throw Configuration (Pole-Throw)
- Actuator Style = Top
- Actuator Color = Black
- SLS Series

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#)
 [Request Sample](#)
 [Find Similar Products](#)
 [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • SLIDE SWITCH (SLS-131PC) SP3T PC_TERMINALS (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • SWITCHES_CORE_PROGRAM_CATALOG (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Configuration (Pole-Throw) = Single Pole - Three Throw • Actuator Style = Top • Mount Angle = Vertical • Terminal Configuration = Standard • Grade = Economy • Termination Type = PC <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Contact Rating = 150mA @ 12 VDC, 250mA @ 125 VAC <p>Body Related Features:</p> <ul style="list-style-type: none"> • Number of Positions = 3 • Actuator Color = Black • Series = SLS • Mount Style = Through-Hole • PCB Tail Length (mm [in]) = 3.30 [0.130] • Actuator Length (mm [in]) = 5.00 [0.197] • Actuator Material = PBT • Actuator Travel = 3.20 [.126] 	<p>Contact Related Features:</p> <ul style="list-style-type: none"> • Contact Plating = Silver • Contact Base Material = Copper Alloy <p>Housing Related Features:</p> <ul style="list-style-type: none"> • UL Flammability Rating = UL 94-HB <p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Number of Actuators = Single <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C • RoHS/ELV Compliance History = Always was RoHS compliant <p>Identification Marking:</p> <ul style="list-style-type: none"> • Stamped Marking = With <p>Other:</p> <ul style="list-style-type: none"> • Brand = Tyco Electronics



Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address

Follow Us On:

[Twitter](#) [Facet](#) [Flickr](#) [Linke](#) [YouTi](#)

Visit Us On:



[Provide Website Feedback](#)