

This browser does not have Java enabled.



Search by Keyword or Part # 

[Products](#) | [Documentation](#) | [Resources](#) | [My Account](#) | [Customer Support](#)

[Home](#) > [Products](#) > [Switches & Knobs](#) > [Product Feature Selector](#) > Product Details

1-1825910-5 Product Details

Have a Question?

Chat with a Product Information Specialist



1-1825910-5

TE Internal Number: 1-1825910-5

 [Active](#)

Pushbutton Switches

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Switch - Mechanical
- Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 50mA
- Operating Function = Off [On]

[View all Features](#)

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[Click to customize your PDFs](#)

pdfcrowd.com

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch - Mechanical
- Tactile = Yes
- Configuration (Pole-Throw) = Single Pole - Single Throw
- Mount Angle = Vertical
- Termination Type = Printed Circuit
- Actuator Style = Round

Electrical Characteristics:

- Contact Rating = 50mA

Body Related Features:

- [Series](#) = FSM
- Mount Style = Through-Hole
- Actuator Length (mm [in]) = 5.90 [0.232]
- Actuator Profile = Extended
- Actuator Color = Red
- Case Material = Nylon
- Actuator Material = PBT

Contact Related Features:

- Contact Plating = Silver

Housing Related Features:

- Process Sealed = No
- Low Profile = No

Configuration Related Features:

- Operating Function = Off [On]
- Ganged = No
- ESD Grounding Terminal = Without
- Actuator Force (g [oz]) = 260.00 [9.178]
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Temperature Rating = High

Packaging Related Features:

- Packaging Method = Loose Piece

Other:

- Brand = Alcoswitch
- Comment = (On) indicates momentary position.



[Corporate Information](#)

[Quick Links](#)

[Customer Support](#)

[Sign up for our eNewsletter](#)


[Click to customize your PDFs](#)

pdfcrowd.com

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)

Follow Us On:



Visit Us On:



[Click to customize your PDFs](#)

[pdfcrowd.com](#)