

Representative photograph, actual product appearance may vary.

- [▶ Terminal Identification](#)
- [▶ Panel Cutout](#)
- [▶ Accessory: Seals](#)
- [▶ Accessory: Nuts](#)
- [▶ Specifications](#)

[Click here for a print friendly version of this datasheet.](#)

## 1TL1-3G

TL Series Toggle Switch, 1 pole, 2 position, Screw terminal, Locking Lever, Military Part Number MS24658-23G

### Features

- Qualified to MIL-S-3950
- Environment-proof sealing
- 1,2, and 4 pole circuitry
- Standard and pull-to-unlock levers
- 2 and 3 position, maintained and momentary toggle action
- Temperature range: -85°F to +160°F
- Completely sealed switching chamber
- Step-design case provides added space between terminals to help prevent shorting
- UL recognized, CSA certified
- CE approved


### Typical Applications

- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

### Description

TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Product Specifications	
Product Type	Toggle
Ampere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc, 0.5 A to 15 A at 0.5 Vac to 277 Vac, 0.5 A to 20 A at 0.5 Vdc to 28 Vdc, 0.75 A at 115 Vdc
Circuitry	SPDT
Action	2 position
Circuitry/Operating action	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p><b>Keyway Position</b></p> </div> <div style="text-align: center;"> <p><b>Opposite Keyway Position</b></p> </div> </div>
Mounting	Bushing 15/32 in
Termination	Screw
Military Part Number	MS24658-23G

<b>Lever Type</b>	Locking
<b>Lever Lock</b>	 <p>Locked in extreme position (Keyway side)</p>
<b>UL/CSA Rating Code</b>	L191: 15 A-125, 250, 277 Vac; 1/2 Hp-125 Vac; 1 Hp-250, 277 Vac; 5 A-120 Vac "L"
<b>Comment</b>	Silver cadmium oxide contacts
<b>Availability</b>	Global
<b>UNSPSC Code</b>	30211908
<b>UNSPSC Commodity</b>	30211908 Toggle switches
<b>Series Name</b>	TL Series

*Due to regional agency approval requirements, some products may not be available in your area. Please contact your regional Honeywell office regarding your product of choice.*