

**Quick Reference**

Search by part #

Check distributor part inventory

**Products**

Browse Products

-By Device -

-By Product Line-

-Attachment Methods-

-Interface Materials -

-Accessories -

**Useful Links**

[MSDS Safety Sheets](#)

[How to order?](#)

[Find Sales Rep](#)

[Find Distributor](#)

[Sample Request](#)

[Quote Request](#)

[Catalog Request](#)

[Building a part #](#)

[Part # Cross Ref](#)

## TAPE Attachment Method

Part Number: 364424B00032G



Printer Friendly Version  
Download our BGA Brochure (PDF)


**This is a popular item and should be available at Aavid Thermalloy's authorized distributors**

Find your [local distributor](#)

BGA Surface	Tape Type	Heat Sink Finish
Metal	<a href="#">T405R</a>	Black Anodize


### Features and Benefits

- Tape mounting saves board space by eliminating mounting holes
- Convenient peel and stick assembly is quick and clean
- Pin Fin array allows omnidirectional airflow to maximize heat dissipation



Width	Length	Height	Fin Thickness Across Width	Fin Thickness Across Length	Base Thickness	# of fins across width	# of fins across length
40.1mm	40mm	11.4mm	1.02mm	0.89mm	2.54mm	13	13


### Mechanical Outline Drawing



Unless otherwise shown, tolerances are  $\pm 0.38( \pm .015)$

### Thermal Performance

* ? n	** ? f
18.4	6.02



\* Natural convection thermal resistance is based on a 75 °C heat sink temperature rise.

\*\* Forced convection thermal resistance based on an entering 1.0 m/s (200 fpm) airflow. Due to various heat dissipation paths within a BGA device, please test the heat sink in your application.

This data sheet represents only one of a broad range of products we make to cool electronics. Our representatives can help you configure a complete cooling solution for your individual applications.

For more information on how to put our strengths to work for you, contact your local sales representative:  
<http://www.aavidthermalloy.com/sales/rep.shtml>