

## KHX5300S2LLK2/2G

### 2GB (1GB 128M x 64-Bit x 2 pcs.)

### PC2-5300 CL4 200-Pin SODIMM Kit

#### DESCRIPTION:

Kingston's KHX5300S2LLK2/2G is a kit of two 128M x 64-bit 1GB (1024MB) DDR2-667 CL4 SDRAM (Synchronous DRAM) memory modules, based on sixteen 64M x 8-bit DDR2 FBGA components (per module). Total kit capacity is 2GB (2048MB). Each pair has been tested to run at DDR2 667MHz at low latency timing of 4-4-4-12 at 1.8V. The SPDs are programmed to JEDEC latency timing of 4-4-4-12 at 1.8V. Each 200-pin SODIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:


#### FEATURES:

- ✓ Power supply : Vdd: 1.8V ± 0.1V, Vddq: 1.8V ± 0.1V
- ✓ Double-data-rate architecture; two data transfers per clock cycle
- ✓ Bidirectional data strobe(DQS)
- ✓ Differential clock inputs(CK and CK)
- ✓ DLL aligns DQ and DQS transition with CK transition
- ✓ Programmable Read latency 3, 4 (clock)
- ✓ Burst Length: 4, 8 (Interleave/nibble sequential)
- ✓ Programmable Burst type (sequential & interleave)
- ✓ Timing Reference: 4-4-4-12 at +1.8V
- ✓ Edge aligned data output, center aligned data input
- ✓ Auto & Self refresh, 7.8us refresh interval (8K/64ms refresh)
- ✓ Serial presence detect with EEPROM
- ✓ PCB : Height 1.180" (30.00mm), double sided component


#### PERFORMANCE:

- |   |                                |
|---|--------------------------------|
| ✓ Clock Cycle Time (tCK) CL=4                   | 3ns (min.) / 8ns (max.)        |
| ✓ Row Cycle Time (tRC)                          | 60ns (min.)                    |
| ✓ Refresh to Active/Refresh Command Time (tRFC) | 105ns                          |
| ✓ Row Active Time (tRAS)                        | 36ns (min.) / 70,000ns (max.)  |
| ✓ Single Power Supply of                        | +1.8V (+/- .1V)                |
| ✓ Power   | 1.800 W (operating per module) |
| ✓ UL Rating                                     | 94 V - 0                       |
| ✓ Operating Temperature                         | 0° C to 55° C                  |
| ✓ Storage Temperature                           | -55° C to +125° C              |



**MODULE DIMENSIONS:**

(units = millimeters)

**For more information, go to [www.kingston.com](http://www.kingston.com)**

All Kingston products are tested to meet our published specifications. Some motherboards or system configurations may not operate at the published HyperX memory speeds and timing settings. Kingston does not recommend that any user attempt to run their computers faster than the published speed. Overclocking or modifying your system timing may result in damage to computer components.