

Memory Module Specification

KVR400D2S4R3K2/4G

4GB (2GB 256M x 72-Bit x 2 pcs.) DDR2-400 CL3 Registered 240-Pin ECC DIMM Kit

DESCRIPTION:

ValueRAM's KVR400D2S4R3K2/4G is a kit of two 256M x 72-bit 2GB (2048MB) DDR2-400 CL3 SDRAM (Synchronous **DRAM**) "single rank" registered ECC memory modules. Total kit capacity is 4GB (4096MB). The components on each module include eighteen 256M x 4-bit (32M x 4-bit x 8 Bank) DDR2-400 SDRAM in FBGA packages. Each 240-pin DIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

FEATURES:

\blacksquare	Clock Cycle Time (tCK) CL=3	5ns (min.) / 8ns (max.)
	Row Cycle Time (tRC)	60ns (min.)
	Refresh to Active/Refresh Command Time (tRFC)	127.5ns
	Row Active Time (tRAS)	45ns (min.) / 70,000ns (max.)
	Single Power Supply of	+1.8V (+/1V)
	Power	3.888 W (operating per module)
	UL Rating	94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.250" (31.75mm).




Figure 1: KVR400D2S4R3K2/4G 240-Pin DIMM