

4, 6 and 8 Channel EMI Filter Arrays with ESD Protection

Features

- Four, six and eight channels of EMI filtering with ESD protection
- Pi-style EMI filters in a capacitor-resistor-capacitor (C-R-C) network
- $\pm 15\text{kV}$ ESD protection (IEC 61000-4-2, contact discharge)
- $\pm 30\text{kV}$ ESD protection (HBM)
- Greater than 25dB of attenuation from 800MHz to 3GHz
- UDFN package with 0.40mm lead pitch:
 - 4-ch. = 8-lead UDFN
 - 6-ch. = 12-lead UDFN
 - 8-ch. = 16-lead UDFN
- Tiny UDFN package size:
 - 8-lead: 1.7mm x 1.35mm x 0.5mm
 - 12-lead: 2.5mm x 1.35mm x 0.5mm
 - 16-lead: 3.3mm x 1.35mm x 0.5mm
- Increased robustness against vertical impacts during manufacturing process
- Lead-free finishing

Applications

- I/O port protection for mobile handsets, notebook computers, PDAs etc.
- EMI filtering for data ports in cell phones, PDAs or notebook computers.
- EMI filtering for LCD, camera and chip-to-chip data lines


Product Description

California Micro Devices's CM1637 is an EMI filter array with ESD protection, which integrates either four, six or eight pi filters (C-R-C). Each CM1637 filter has component values of 7.5pF - 200Ω - 7.5pF . These parts include ESD protection diodes on every pin, providing a very high level of protection for sensitive electronic components that may be subjected to electrostatic discharge (ESD). The ESD diodes connected to the filter ports safely dissipate ESD strikes of $\pm 15\text{kV}$ contact discharge, twice the specification requirement of the IEC 61000-4-2, Level 4 international standard. Using the MIL-STD-883 (Method 3015) specification for Human Body Model (HBM) ESD, the pins are protected for contact discharges at greater than $\pm 30\text{kV}$.

This device is particularly well-suited for portable electronics (e.g. mobile handsets, PDAs, notebook computers) because of its small package and easy-to-use pin assignments. In particular, the CM1637 is ideal for EMI filtering and protecting data lines from ESD in wireless handsets.


The CM1637 is available in space-saving, ultra-low-profile, 8-lead, 12-lead and 16-lead 0.4mm pitch UDFN packages. It is fabricated with California Micro Devices' *Centurion*TM process and available with lead-free finishing. This new small UDFN package provides up to 42% board space savings vs. the 0.50mm pitch UDFN packages.

Electrical Schematic



1 of 4/6/8 EMI Filtering + ESD Channels

* See Package/Pinout Diagram for expanded pin information.

PACKAGE / PINOUT DIAGRAMS

PIN DESCRIPTIONS

Pins			NAME	DESCRIPTION	Pins			NAME	DESCRIPTION
1637-04Dx	1637-06Dx	1637-08Dx			1637-04Dx	1637-06Dx	1637-08Dx		
1	1	1	FILTER1	Filter Channel 1	8	12	16	FILTER1	Filter Channel 1
2	2	2	FILTER2	Filter Channel 2	7	11	15	FILTER2	Filter Channel 2
3	3	3	FILTER3	Filter Channel 3	6	10	14	FILTER3	Filter Channel 3
4	4	4	FILTER4	Filter Channel 4	5	9	13	FILTER4	Filter Channel 4
	5	5	FILTER5	Filter Channel 5		8	12	FILTER5	Filter Channel 5
	6	6	FILTER6	Filter Channel 6		7	11	FILTER6	Filter Channel 6
		7	FILTER7	Filter Channel 7			10	FILTER7	Filter Channel 7
		8	FILTER8	Filter Channel 8			9	FILTER8	Filter Channel 8
GND Pad			GND	Device Ground					

Ordering Information
PART NUMBERING INFORMATION

Leads/Pins	Package	Lead-free Finish	
		Ordering Part Number ¹	Part Marking
8	UDFN-08	CM1637-04DE	GE
12	UDFN-12	CM1637-06DE	P37E
16	UDFN-16	CM1637-08DE	P378E

Note 1: Parts are shipped in Tape & Reel form unless otherwise specified.

Specifications

ABSOLUTE MAXIMUM RATINGS

PARAMETER	RATING	UNITS
Storage Temperature Range	-65 to +150	°C
DC Power per Resistor	100	mW
Package DC Power Rating	300	mW

STANDARD OPERATING CONDITIONS

PARAMETER	RATING	UNITS
Operating Temperature Range	-40 to +85	°C

ELECTRICAL OPERATING CHARACTERISTICS (SEE NOTE 1)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
R	Resistance		160	200	240	Ω
C _{TOTAL}	Total Channel Capacitance	At 2.5VDC Reverse Bias, 1MHz, 30mVAC	12	15	18	pF
C	Capacitance	At 2.5V DC, 1MHz, 30mV AC		7.5		pF
V _{DIODE}	Diode Standoff Voltage	I _{DIODE} = 10μA		6.0		V
I _{LEAK}	Diode Leakage Current (reverse bias)	V _{DIODE} = 3.3V		0.1	1	μA
V _{SIG}	Signal Voltage Positive Clamp Negative Clamp	I _{LOAD} = 10mA I _{LOAD} = -10mA	5.6 -0.4	6.8 -0.8		V V
V _{ESD}	In-system ESD Withstand Voltage a) Human Body Model, MIL-STD-883, Method 3015 b) Contact Discharge per IEC 61000-4-2 Level 4	Notes 2 and 3	±30 ±15			kV kV
f _C	Cut-off Frequency Z _{SOURCE} =50Ω, Z _{LOAD} =50Ω	R = 200Ω, C = 15pF; Note 3		210		MHz
A _{1GHz}	Absolute Attenuation @ 1GHz from 0dB Level	Z _{SOURCE} = 50Ω, Z _{LOAD} = 50Ω, DC Bias = 0V; Notes 1, 4 and 5		32		dB
A _{800MHz - 6GHz}	Absolute Attenuation @ 800MHz to 6GHz from 0dB Level	Z _{SOURCE} = 50Ω, Z _{LOAD} = 50Ω, DC Bias = 0V; Notes 1, 4 and 5		27		dB

Note 1: T_A=25°C unless otherwise specified.

Note 2: ESD applied to input and output pins with respect to GND, one at a time.

Note 3: These parameters are guaranteed by design and characterization.

Note 4: Attenuation / RF curves characterized by a network analyzer using microprobes.

Note 5: These parameters are NOT guaranteed by design, characterization and production.

Performance Information

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 1. Insertion Loss vs. Frequency (FILTER1 Input to GND, CM1637-04DE)




Figure 2. Insertion Loss vs. Frequency (FILTER2 Input to GND, CM1637-04DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 3. Insertion Loss vs. Frequency (FILTER3 Input to GND, CM1637-04DE)




Figure 4. Insertion Loss vs. Frequency (FILTER4 Input to GND, CM1637-04DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 5. Insertion Loss vs. Frequency (FILTER1 Input to GND, CM1637-06DE)




Figure 6. Insertion Loss vs. Frequency (FILTER2 Input to GND, CM1637-06DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 7. Insertion Loss vs. Frequency (FILTER3 Input to GND, CM1637-06DE)




Figure 8. Insertion Loss vs. Frequency (FILTER4 Input to GND, CM1637-06DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 9. Insertion Loss vs. Frequency (FILTER5 Input to GND, CM1637-06DE)




Figure 10. Insertion Loss vs. Frequency (FILTER6 Input to GND, CM1637-06DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 11. Insertion Loss vs. Frequency (FILTER1 Input to GND, CM1637-08DE)




Figure 12. Insertion Loss vs. Frequency (FILTER2 Input to GND, CM1637-08DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 13. Insertion Loss vs. Frequency (FILTER3 Input to GND, CM1637-08DE)




Figure 14. Insertion Loss vs. Frequency (FILTER4 Input to GND, CM1637-08DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^{\circ}\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 15. Insertion Loss vs. Frequency (FILTER5 Input to GND, CM1637-08DE)




Figure 16. Insertion Loss vs. Frequency (FILTER6 Input to GND, CM1637-08DE)

Performance Information (cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 17. Insertion Loss vs. Frequency (FILTER7 Input to GND, CM1637-08DE)




Figure 18. Insertion Loss vs. Frequency (FILTER8 Input to GND, CM1637-08DE)

Performance Information (cont'd)




Figure 19. Filter Capacitance vs. Input Voltage over Temperature (normalized to capacitance at 2.5VDC and 25°C)


Mechanical Details

UDFN-08 Mechanical Specifications

Dimensions for the CM1637 supplied in a 8-lead, 0.4mm pitch UDFN package are presented below.

PACKAGE DIMENSIONS						
Package	uDFN					
JEDEC No.	MO-229C*					
Leads	8					
Dim.	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A	0.45	0.50	0.55	0.018	0.020	0.022
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	0.127 REF			0.005 REF		
b	0.15	0.20	0.25	0.006	0.008	0.010
D	1.60	1.70	1.80	0.063	0.067	0.071
D2	1.10	1.20	1.30	0.043	0.047	0.051
E	1.25	1.35	1.45	0.049	0.053	0.057
E2	0.30	0.40	0.50	0.012	0.016	0.020
e	0.40 BSC			0.016 BSC		
K	0.22 REF			0.009 REF		
L	0.15	0.25	0.35	0.006	0.010	0.014
# per tape and reel	3000 pieces					
Controlling dimension: millimeters						


*This package is compliant with JEDEC standard MO-229C with the exception of the D, D2, E, E2, K and L dimensions as called out in the table above.



Dimensions for 8-Lead, 0.4mm pitch uDFN package

Tape and Reel Specifications

PART NUMBER	PACKAGE SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P_0	P_1
CM1637-04DE	1.70 X 1.35 X 0.50	1.95 X 1.60 X 0.60	8mm	178mm (7")	3000	4mm	4mm




Mechanical Details (cont'd)

UDFN-12 Mechanical Specifications

Dimensions for the CM1637 supplied in a 12-lead, 0.4mm pitch UDFN package are presented below.

PACKAGE DIMENSIONS						
Package	uDFN					
JEDEC No.	MO-229C*					
Leads	12					
Dim.	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A	0.45	0.50	0.55	0.018	0.020	0.022
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	0.127 REF			0.005 REF		
b	0.15	0.20	0.25	0.006	0.008	0.010
D	2.40	2.50	2.60	0.094	0.098	0.102
D2	1.90	2.00	2.10	0.075	0.079	0.083
E	1.25	1.35	1.45	0.049	0.053	0.057
E2	0.30	0.40	0.50	0.012	0.016	0.020
e	0.40 BSC			0.016 BSC		
K	0.22 REF			0.009 REF		
L	0.15	0.25	0.35	0.006	0.010	0.014
# per tape and reel	3000 pieces					
Controlling dimension: millimeters						


*This package is compliant with JEDEC standard MO-229C with the exception of the D, D2, E, E2, K and L dimensions as called out in the table above.



Dimensions for 12-Lead, 0.4mm pitch uDFN package

Tape and Reel Specifications

PART NUMBER	PACKAGE SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P_0	P_1
CM1637-06DE	2.50 X 1.35 X 0.50	2.75 X 1.60 X 0.60	8mm	178mm (7")	3000	4mm	4mm




Mechanical Details (cont'd)

UDFN-16 Mechanical Specifications

Dimensions for the CM1637 supplied in a 16-lead, 0.4mm pitch UDFN package are presented below.

PACKAGE DIMENSIONS						
Package	uDFN					
JEDEC No.	MO-229C*					
Leads	16					
Dim.	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A	0.45	0.50	0.55	0.018	0.020	0.022
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	0.127 REF			0.005 REF		
b	0.15	0.20	0.25	0.006	0.008	0.010
D	3.20	3.30	3.40	0.126	0.130	0.134
D2	2.70	2.80	2.90	0.106	0.110	0.114
E	1.25	1.35	1.45	0.049	0.053	0.057
E2	0.30	0.40	0.50	0.012	0.016	0.020
e	0.40 BSC			0.016 BSC		
K	0.22 REF			0.009 REF		
L	0.15	0.25	0.35	0.006	0.010	0.014
# per tape and reel	3000 pieces					
Controlling dimension: millimeters						

*This package is compliant with JEDEC standard MO-229C with the exception of the D, D2, E, E2, K and L dimensions as called out in the table above.



Dimensions for 16-Lead, 0.4mm pitch uDFN package

Tape and Reel Specifications

PART NUMBER	PACKAGE SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P_0	P_1
CM1637-08DE	3.30 X 1.35 X 0.50	3.50 X 1.55 X 0.70	12mm	178mm (7")	3000	4mm	4mm

