



LEAD FINISH: GOLD PL.	
CASING FINISH: GOLD PL.	
CAPACITANCE	.015 μ F
TEMP. RANGE	-55°C TO 125°C
CURRENT	5 AMP MAX.
WORKING VOLTAGE	85°C -- VDC MAX. 125°C 50VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1	7
10	25
100	40
1 GHz	60
10 GHz	60



MARKING:
 PART: COLOR DOT:
 PINK
 BAG: SCIF-9900-153
 XXXX DATE CODE
 LOT NO.
 QTY./BAG (200 MAX.)

- NOTES:
 1. SUGGESTED MOUNTING HOLE = ϕ .130
 2. MAX SOLDERING TEMP = 235°C FOR 5 SEC. MAX
 3. THIS A LEAD FREE PRODUCT



		00	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 SPECTRUM CONTROL INC.	ERIE, FAIRVIEW PENNSYLVANIA
		CN 55226-ENG	CHANGE NOTICE	Fractions \pm 1/64 Dec. .xx \pm Dec. .xxx \pm .005 Angles \pm 0° 30' CODE IDENT. NO. DLSP2		DwnDONALDSON Ckd. 8/6/10 Apvd. Scale NONE