



Dimensions (In.)

Specifications:

- Tolerance: ±3%
- Leads: 22AWG

| Mouser Stock No. | L (μH) ±3% | Q Min. | Test Freq. (kHz) | Min. S.R.F. (MHz) | D.C.R. Max. (Ω) | Max. DC Current (mA) | Coil Form |
|------------------|------------|--------|------------------|-------------------|-----------------|----------------------|-----------|
| 43HG337 | 0.33 | 45 | 25.0 | 360 | 0.09 | 1400 | Phenolic |
| 43HG397 | 0.39 | 45 | 25.0 | 310 | 0.12 | 1225 | Phenolic |
| 43HG687 | .068 | 45 | 25.0 | 310 | 0.12 | 1225 | Phenolic |
| 43HG106 | 1.0 | 50 | 25.0 | 200 | 0.29 | 785 | Phenolic |
| 43HG226 | 2.2 | 33 | 7.9 | 135 | 0.95 | 435 | Phenolic |
| 43HG276 | 2.7 | 33 | 7.9 | 120 | 1.20 | 385 | Phenolic |
| 43HG336 | 3.3 | 33 | 7.9 | 110 | 2.00 | 300 | Phenolic |
| 43HG476 | 4.7 | 33 | 7.9 | 90 | 2.60 | 260 | Phenolic |
| 43HG105 | 10 | 55 | 7.9 | 45 | 0.90 | 290 | Ferrite |
| 43HG155 | 15 | 65 | 2.5 | 40 | 1.40 | 240 | Ferrite |
| 43HG225 | 22 | 75 | 2.5 | 30 | 2.50 | 175 | Ferrite |
| 43HG335 | 33 | 65 | 2.5 | 19 | 3.00 | 165 | Ferrite |
| 43HG395 | 39 | 60 | 2.5 | 14.5 | 2.60 | 176 | Ferrite |
| 43HG475 | 47 | 55 | 2.5 | 13 | 2.75 | 170 | Ferrite |
| 43HG685 | 68 | 55 | 2.5 | 11 | 3.30 | 156 | Ferrite |
| 43HG104 | 100 | 50 | 2.5 | 9.5 | 4.50 | 133 | Ferrite |
| 43HG154 | 150 | 65 | .79 | 8 | 6.05 | 114 | Ferrite |
| 43HG224 | 220 | 65 | .79 | 6.2 | 7.45 | 103 | Ferrite |
| 43HG474 | 470 | 65 | .79 | 3.9 | 17.9 | 100 | Ferrite |
| 43HG103 | 1000 | 55 | .79 | 2.3 | 33.1 | 74 | Ferrite |