



Dimensions (In.)

Specifications:

- Tolerance: $\pm 10\%$
- Leads: 22AWG
- MIL-Spec: MIL-C-15305

Mouser Stock No.	L (μH) $\pm 10\%$	Q Min.	Test Freq. (kHz)	Min. S.R.F. (MHz)	D.C.R. Max. (Ω)	Max. DC Current (mA)	Coil Form
43HH106	1.0	50	25.0	200	0.29	785	Phenolic
43HH226	2.2	33	7.9	135	0.95	435	Phenolic
43HH276	2.7	33	7.9	120	1.20	385	Phenolic
43HH336	3.3	33	7.9	110	2.00	300	Phenolic
43HH476	4.7	33	7.9	90	2.60	260	Phenolic
43HH105	10	55	7.9	45	0.90	290	Ferrite
43HH155	15	65	2.5	40	1.40	240	Ferrite
43HH225	22	75	2.5	30	2.50	175	Ferrite
43HH335	33	65	2.5	19	3.00	165	Ferrite
43HH395	39	60	2.5	14.5	2.60	176	Ferrite
43HH475	47	55	2.5	13	2.75	170	Ferrite
43HH685	68	55	2.5	11	3.30	156	Ferrite
43HH825	82	50	2.5	10.3	3.90	143	Ferrite
43HH104	100	50	2.5	9.5	4.50	133	Ferrite
43HH154	150	65	.79	8	6.05	114	Ferrite
43HH224	220	65	.79	6.2	7.45	103	Ferrite
43HH474	470	65	.79	3.9	17.9	100	Ferrite
43HH103	1000	55	.79	2.3	33.1	74	Ferrite