



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. TERMINAL NUMBERS FOR REF. ONLY
 3. CONTACT MATERIAL: SILVER
 4. CONTACT RATING: 20mA; 15VDC
 5. TRAVEL: 0.15 ±0.1mm
 - ▲ 6. OPERATING FORCE: 100± 50 GRAMS
 7. ELECTRICAL LIFE: 100,000 CYCLES
 8. CONTACT RESISTANCE: 500mΩ MAX.
 9. ▲ DENOTES CRITICAL PARAMETER
 10. BOUNCE: 10m SECONDS MAX
 11. INSULATION RESISTANCE: 100MΩ MIN.
 12. DIELECTRIC STRENGTH: 250VAC FOR 1 MINUTE WITH NO BREAK DOWN
 13. 2002/95/EC (ROHS) COMPLIANT; HALOGEN FREE
 14. PACKAGING: TAPE & REEL, 8000 PARTS PER REEL.



B	196700	UPDATE RATING	02/22/11	BMA
A	19657	New Release	2/7/11	BGL
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL3700AF100QG				
SCALE	DATE	DR	DWG	REV
10:1	2/7/2011	BGL	P003001	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED