

MICROOPTO
MOS 24VDC/5-48VDC 0,5A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com



Electronic CO contacts are used anywhere output signals need to be changed over. For this purpose, the input signal is directly switched through to the output side and inverted; as a result, the opto module can also be used as a pure inverter. The advantage over electromechanical relays lies in the wear-free switching and the possibility of realising high switching frequencies.

General ordering data

Order No.	8937980000
Part designation	MOS 24VDC/5-48VDC 0,5A
Version	MICROOPTO, Optos, 5...48 V DC, 500 mA, Screw connection
GTIN (EAN)	4032248716210
Qty.	1 pc(s).

Creation date October 15, 2010 8:49:41 AM CEST

Last update 30.08.2010 / We reserve the right to make technical changes.

MICROOPTO
MOS 24VDC/5-48VDC 0,5A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Technical data

Dimensions

Length	90 mm	Width	6.1 mm
Height	98 mm		

Temperature

Ambient temperature (operational)	-25 °C...+60 °C	Storage temperature	-40 °C...+80 °C
-----------------------------------	-----------------	---------------------	-----------------

Probability of failure

MTTF	620 Years
------	-----------

Approvals

Approvals institutes	CULUS; GERMLLOYD; GOSTME25; CE
----------------------	-----------------------------------

Control side

Dropout voltage	< 50 % U _{nenn}	Input frequency	1 kHz
Power rating	160 mW	Protective circuit, control side	Varistor, reverse polarity protection
Rated control voltage	24 V DC ±20 %	Status display on control side	Green status LED
making voltage	> 80 % U _{nenn}		

General data

Standards	EN 50178 GL 2003-VI-Abs. 9 IEC 62314 UL508	Humidity	40°C / 93% rel. humidity, no condensation
Flammability class UL 94	V-0	Conductor connection system	Screw connection
Solid-state type	Transistor		

Insulation coordination (EN 50 178)

Clearance and creepage distances for control/load side	> 3 mm	Overvoltage category	III
Pollution severity	2	Rated impulse withstand voltage	4 kV (1.2 / 50 µs)
Rated voltage	300 V		

Load side

Continuous current	500 mA	Leakage current	< 2 µA
Load category	LC A	Protective circuit, load side	Integrated free-wheel diode
Rated switching current	500 mA	Rated switching voltage	5...48 V DC
Short-circuit-proof	No	Switch-off delay	< 50 µs
Switch-on delay	< 40 µs	Voltage drop at max. load	Max. 1 V

Classifications

ETIM 3.0	EC001504	eClass 5.1	27-27-09-90
eClass 6.0	27-27-09-90		

Creation date October 15, 2010 8:49:41 AM CEST

Last update 30.08.2010 / We reserve the right to make technical changes.

MICROOPTO
MOS 24VDC/5-48VDC 0,5A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings

Electric symbol

