

(1,27mm) .050"
PCMT, PCMS SERIES

PCMCIA TERMINAL & SOCKET STRIPS

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?PCMT

Insulator Material: Black Liquid Crystal Polymer
Terminal Material: Phosphor Bronze
Plating: Sn or Au over 50µ" (1,27µm) Ni
Current Rating: 2A @ 80°C ambient
Operating Temp Range: -55°C to +105°C with Tin; -55°C to +125°C with Gold
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0,15mm) .006" max
RoHS Compliant: Yes



PCMT - 134 - LEAD STYLE - PLATING OPTION - D - RA - CARD LENGTH - SL

Mates with: PCMS

Specify LEAD STYLE from chart


-L
 = 10µ" (0,25µm) Gold on post, Matte Tin on tail

-S
 = 30µ" (0,76µm) Gold on post, Matte Tin on tail

-01
 = (25,40mm) 1.00" Card Length

-02
 = (50,80mm) 2.00" Card Length

-03
 = (76,20mm) 3.00" Card Length



APPLICATION

Reflowed solder forced into lock notch

Plated Through-hole Plastic Solder Lock

Note: Some lengths, styles and options are non-standard, non-returnable.

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?PCMS

Insulator Material: Black Liquid Crystal Polymer
Contact Material: BeCu
Plating: Au or Sn over 50µ" (1,27µm) Ni
Current Rating: 1A
Operating Temp Range: -55°C to +125°C
Contact Resistance: 10 mΩ max
Insertion Depth: (3,05mm) .120" min
Insertion Force: (Single contact only) 4.0oz (1,11N) avg.
Withdrawal Force: (Single contact only) 3.0oz (0,83N) avg. 3.0oz (0,83N) avg.
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0,10mm) .004" max
RoHS Compliant: Yes



PCMS - 134 - CARD THICKNESS - PLATING OPTION - D


Mates with: PCMT

-01
 = (0,80mm) .031" thick board

-02
 = (1,60mm) .062" thick board

-L
 = 10µ" (0,25µm) Gold on contact, Matte Tin on tail

-S
 = 30µ" (0,76µm) Gold on contact, Matte Tin on tail



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8990337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600
 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109
 Downloaded from Elcodis.com electro SAMTEC HONG KONG • Tel: 852-2690-9858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112