

Search Results

Home > Products Overview > Search Results >

Evaluate

- FAQ's

Design a Solution

- Part Drawings

- PDF Split Bolt, ..


How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'SBC500-1'

Your search criteria matched only one product, shown below

**SBC500-1**



For Use with Copper Code Conductors

- Made from high strength copper alloy to resist corrosion and provide premium electrical and mechanical performance
- Offered with extra long body to allow connection of one or two taps to a single run conductor
- Wide wire range -taking capability minimizes inventory requirements
- Nut hex provides correct fit with socket, box, or open end wrenches resulting in proper torquing of electrical connection
- Pressure bar provides secure connection on a full range of conductor combinations used with each connector assuring premium wire pull -out strength
- UL Listed and CSA Certified for use up to 600 V and temperature rated 90°C

Part Number	SBC500-1
RoHS Compliancy Status	Compliant
Part Description	Copper split bolt connector, type SBC.
Product Type	Mechanical Connectors- Split Bolt
CSA Certified	Yes
UL Listed	Yes
Length (In.)	2.83
Length (mm)	74.4
Min. Tap with One Max. Run	2/0 STR
Range of Equal Run & Tap Min.	300 kcmil
Range of Equal Run and Tap Max.	500 kcmil
Body Hex	1.33
Inside Diameter (In.)	.81
Nut Hex	1.74
Pricing Description	Split Bolt, Copper, 300- 500 kcmil
Tightening Torque (InLbs)	825
Tightening Torque (Nm)	(93.2)
Wire Range (mm <sup>2</sup> )	10 – 240
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.