

GSM | GPRS

GC864-QUAD
Compact

GC864-PY
Compact



	Ultra Compact
	Telit Unified AT Command Set
	Telit Unified Form Factor
	Quad Band GPRS
	GPRS Class 10
	RoHS Compliant
	SIM Access Profile
	PYTHON* Script Interpreter
	80 Pin Connector
	Embedded FTP and SMTP Client
	Extended Temperature Range
	Extended RF Sensitivity
	Serial Port Multiplexer (GSM 7.10)
	Embedded TCP/IP Stack
optional	
	Integrated SIM holder



TELIT INFINITA SERVICES



The new GC864 product family is one of the smallest GSM/GPRS quad-band modules with industrial connectors in the market.

With its ultra-compact design and extended temperature range, the Telit GC864-QUAD is the perfect platform for medium-volume m2m applications and mobile data devices. Additional features such as integrated TCP/IP protocol stack, SIM Holder on the board (only for GC864-QUAD with SIM holder variant) and serial multiplexer give extend functionality of the application at no additional cost.

The GC864-PY makes it possible to run the customer's application inside the module, thus making it one of the smallest, complete platforms for m2m solutions. State-of-the-art SPI and IIC interfaces provide connectivity to external peripherals such as sensors and displays.

All Telit modules, support Over-the-Air firmware update by means Premium FOTA Management. By embedding RedBend's vCurrent® agent, a proven and battle-tested technology powering hundreds of millions of cellular handsets world-wide Telit is able to update its products by transmitting only a delta file, which represents the difference between one firmware version and another.

As a part of Telit's corporate policy of environmental protection, all products comply to the RoHS (Restriction of Hazardous Substances) directive of the European Union (EU Directive 2002/95/EG).

Product features

- Quad-band EGSM 850 / 900 / 1800 / 1900 MHz
- Output power
 - Class 4 (2W) @ 850 / 900 MHz
 - Class 1 (1W) @ 1800 / 1900 MHz
- Control via AT commands according to GSM 07.05, 07.07 and Telit enhancements
- Serial port multiplexer GSM 7.10
- SIM access profile
- Supply voltage range: 3.22–4.5 V DC (3.8 V DC recommended)
- TCP/IP stack access via AT commands
- Power consumption (typical values)
 - Power off: < 26 uA
 - Idle (registered, power saving): 2.6 mA
 - Dedicated mode: 200 mA
 - GPRS cl.10: 370 mA
- Sensitivity:
 - 107 dBm (typ.) @ 850 / 900 MHz
 - 106 dBm (typ.) @ 1800 / 1900 MHz
- Dimensions: 30 x 36.2 x 3.2 mm
- Weight: 6.1 grams
- Extended temperature range
 - 40°C to +85°C (operational)
 - 40°C to +85°C (storage temperature)
- RoHS compliant



Making machines talk.®

GC864-QUAD

Compact

GC864-PY

Compact



actual size GC864-QUAD

GC864-QUAD with SIM holder

Copyright © 2010, Telit
Subject to changes in technology, design and availability

* Copyright © 1991-1995 by Stichting Mathematisch Centrum, Amsterdam, The Netherlands; All Rights Reserved. Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved. Copyright © 2001-2010 Python Software Foundation; All Rights Reserved. All Rights Reserved are retained in Python.

Distributed by:

Interfaces

- 80-pin Molex connector
- 22 I/O ports maximum
- Analog audio (balanced and unbalanced)
- 3 A/D plus 1 D/A converter
- Buzzer output
- ITU-T V.24 serial link through UART:
 - CMOS level
 - Baud rate from 300 to 115,200 bps
 - Autobauding from 1,200 to 115,200 bps
- 50 Ohm murata GSC antenna connector

Audio

- Telephony, emergency call
- Half rate, full rate, enhanced full rate and adaptive multi rate voice codecs (HR, FR, EFR, AMR)
- Superior echo cancellation & noise reduction
- Handset & hands-free operations
- DTMF

Approvals

- Fully type approved conforming with R&TTE
- CE, GCF, FCC, PTCRB, IC, Anatel

SMS

- Point-to-point mobile originated and mobile terminated SMS
- Concatenated SMS supported
- SMS cell broadcast
- Text and PDU mode

Circuit switched data transmission

- Asynchronous transparent circuit switched data (CSD) up to 14.4 kbps
- Asynchronous non-transparent CSD up to 9.6 kbps
- V.110

GPRS data

- GPRS class 10
- Mobile station class B
- Coding scheme 1 to 4
- PBCCH support

Fax

- Group 3, class 1

GSM supplementary

- Call forwarding
- Call barring
- Call waiting & call hold
- Advice of charge
- Calling line identification presentation (CLIP)
- Calling line identification restriction (CLIR)
- Unstructured supplementary services mobile originated data (USSD)
- Closed user group

Additional features

- SIM phonebook
- SIM Holder (only for GC864-QUAD variant with SIM holder)
- Fixed dialing number (FDN)
- Real-time clock
- Alarm management
- Battery management
- Network LED support
- IRA character SET, UCS2 and GSMDefault
- Jamming detection & report
- Embedded TCP/IP stack, including TCP, IP, UDP, SMTP and FTP protocols
- PFM (Premium FOTA Management) Over the Air Update
- MUX driver
- RIL driver

Python* application resources (GC864-PY ONLY)

- Python* script interpreter (module takes the application code directly in the Python* language)
- Memory: 1.9 MB of NV memory for the user scripts and 1 MB RAM for the Python* engine usage
- Over-the-air application SW update
- IIC Bus and SPI Bus controlled in Python*

**Telit's EASY features**

- EASY SCAN® automatic scan over GSM frequencies (also without SIM card)

Order-No.

Please contact your Telit representative for order codes and all further information



Telit Communications S.p.A.
Via Stazione di Prosecco, 5/B
I-34010 Sgonico (Trieste), Italy
Tel +39 040 4192 200
Fax +39 040 4192 289
E-Mail: EMEA@telit.com
www.telit.com

Telit Wireless Solutions Inc.
3131 RDU Center Drive, Suite 135
Morrisville, NC 27560, USA
Tel +1 888 846 9773 or +1 919 439 7777
Tel +1 888 846 9774 or +1 919 840 0337
E-Mail: NORTHAMERICA@telit.com
www.telit.com

Telit Wireless Solutions Inc.
Rua Cunha Gago, 700 - cj 81, Pinheiros
São Paulo - SP, 05421001, Brazil
Tel +55 11 2679 4654
Fax +55 11 2679 4654
E-Mail: LATINAMERICA@telit.com
www.telit.com

Telit Wireless Solutions Co., Ltd.
12th FL., Shinyoung Securities Bld.
34-12, Yeouido-dong, Yeongdeungpo-gu
Seoul, 150-884, Korea
Tel. +82 2 368 4600
Fax +82 2 368 4606
E-Mail: APAC@telit.com

