


## Inductors, Subminiature, Shielded, Radial Leaded



### FEATURES

- Classification is grade 1, class B
- Subminiature shielded
- Inductance range is 0.10  $\mu\text{H}$  to 100 000  $\mu\text{H}$
- Printed board mounting facilitated by 0.200" [5.08 mm] grid spacing
- Radial lead fixed inductor
- High Q values
- Unitized epoxy-molded construction
- Shielded construction to allow maximum density packaging
- Compliant to RoHS directive 2002/95/EC


**RoHS**  
COMPLIANT

### ELECTRICAL SPECIFICATIONS

**Inductance Tolerance:**  $\pm 10\%$ 
**Dielectric Strength:** 840  $V_{\text{RMS}}$  at sea level

**Working Voltage:** 300  $V_{\text{DC}}$ 
**Q and SRF Values:** Minimum not less than 80 % of specified value

**Maximum Current:** Based on temperature rise not to exceed 35 °C at + 90 °C ambient

### MECHANICAL SPECIFICATIONS

**Operating Temperature:** - 55 °C to + 125 °C

**Terminal Pull:** 3 pounds

### DENSITY SPECIFICATIONS

**Weight:** 1.5 grams maximum

**Shielding:** 3 % coupling maximum when two units are tested side by side


### ENVIRONMENTAL SPECIFICATIONS

**Moisture:** Per MIL-STD-202, method 106

**Vibration:** Low frequency, 10 Hz to 55 Hz at 0.06" [1.52 mm] maximum total excursion at rate of 1 linear sweep per minute for 2 h repeated for each of three mutually perpendicular planes

**Shock:** 100 g, 6 ms, body mounted

### DIMENSIONS in inches [millimeters]



### STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. ( $\mu\text{H}$ )	TOL. (%)	Q NOM.	TEST FREQ. (MHz)	SRF NOM. (MHz)	DCR MAX. ( $\Omega$ )	RATED DC CURRENT (mA)	INCREMENTAL CURRENT (mA) <sup>(1)</sup>
PC	0.10	$\pm 10$	70	25	> 250	0.030	2500	2500
PC	0.12	$\pm 10$	70	25	> 250	0.030	2500	2500
PC	0.15	$\pm 10$	70	25	> 250	0.030	2500	2500
PC	0.18	$\pm 10$	70	25	> 250	0.035	2400	2400
PC	0.22	$\pm 10$	70	25	> 250	0.038	2300	2300
PC	0.27	$\pm 10$	80	25	> 250	0.040	2200	2200
PC	0.33	$\pm 10$	80	25	> 250	0.040	2200	2200
PC	0.39	$\pm 10$	80	25	250	0.045	2100	2100
PC	0.47	$\pm 10$	80	25	230	0.045	2100	2100
PC	0.56	$\pm 10$	80	25	220	0.050	2000	2000

**Note**
<sup>(1)</sup> **Incremental Current:** The DC current required to cause a 5 % reduction in the nominal inductance value.

**STANDARD ELECTRICAL SPECIFICATIONS**

MODEL	IND. (μH)	TOL. (%)	Q NOM.	TEST FREQ. (MHz)	SRF NOM. (MHz)	DCR MAX. (Ω)	RATED DC CURRENT (mA)	INCREMENTAL CURRENT (mA) <sup>(1)</sup>
PC	0.68	± 10	80	25	190	0.055	1900	1900
PC	0.82	± 10	85	25	180	0.060	1800	1800
PC	1.0	± 10	85	25	160	0.070	1700	1700
PC	1.2	± 10	90	7.9	170	0.085	1670	1670
PC	1.5	± 10	100	7.9	155	0.100	1540	1540
PC	1.8	± 10	115	7.9	135	0.110	1470	1470
PC	2.2	± 10	110	7.9	120	0.120	1410	1410
PC	2.7	± 10	110	7.9	104	0.125	1380	1380
PC	3.3	± 10	90	7.9	93	0.165	1200	1200
PC	3.9	± 10	90	7.9	87	0.180	1135	1135
PC	4.7	± 10	95	7.9	79	0.245	985	985
PC	5.6	± 10	95	7.9	72	0.265	950	950
PC	6.8	± 10	85	7.9	63	0.330	853	853
PC	8.2	± 10	95	7.9	60	0.460	720	720
PC	10	± 10	90	7.9	54	0.640	620	620
PC	12	± 10	120	2.5	37	0.800	545	545
PC	15	± 10	120	2.5	28.8	0.865	520	520
PC	18	± 10	115	2.5	23.8	0.940	504	504
PC	22	± 10	125	2.5	21.3	1.03	460	460
PC	27	± 10	115	2.5	20.6	1.18	418	418
PC	33	± 10	120	2.5	18.6	1.30	398	398
PC	39	± 10	120	2.5	17.7	1.41	385	385
PC	47	± 10	110	2.5	14.9	1.61	350	350
PC	56	± 10	115	2.5	13.9	2.08	330	333
PC	68	± 10	105	2.5	12.9	2.20	320	330
PC	82	± 10	105	2.5	11.7	2.42	300	320
PC	100	± 10	95	2.5	10.5	2.15	333	300
PC	120	± 10	95	0.79	5.6	2.38	316	190
PC	150	± 10	90	0.79	5.2	2.52	306	175
PC	180	± 10	95	0.79	4.9	2.88	288	150
PC	220	± 10	95	0.79	4.6	3.18	273	125
PC	270	± 10	100	0.79	4.2	3.50	260	120
PC	330	± 10	100	0.79	3.55	4.80	222	110
PC	390	± 10	100	0.79	3.45	5.44	209	105
PC	470	± 10	100	0.79	3.2	5.9	201	100
PC	560	± 10	95	0.79	2.9	6.3	194	90
PC	680	± 10	100	0.79	2.7	7.2	181	80
PC	820	± 10	90	0.79	2.5	8.0	172	70
PC	1000	± 10	100	0.79	2.35	12	141	65

**Note**

<sup>(1)</sup> **Incremental Current:** The DC current required to cause a 5 % reduction in the nominal inductance value.

**MARKING**

- Manufacturer data printed

**ORDERING INFORMATION**

PC MODEL	0.10 μH INDUCTANCE VALUE	10 % INDUCTANCE TOLERANCE	EB PACKAGE CODE	e2 JEDEC LEAD (Pb)-FREE STANDARD
----------	--------------------------	---------------------------	-----------------	----------------------------------

**GLOBAL PART NUMBER**

<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 2px;">P</div> <div style="border: 1px solid black; padding: 2px;">C</div> <div style="border: 1px solid black; padding: 2px;">9</div> </div> <p>MODEL</p>	<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 2px;">E</div> <div style="border: 1px solid black; padding: 2px;">B</div> </div> <p>PACKAGE CODE</p>	<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 2px;">R</div> <div style="border: 1px solid black; padding: 2px;">1</div> <div style="border: 1px solid black; padding: 2px;">0</div> </div> <p>INDUCTANCE VALUE</p>	<div style="border: 1px solid black; padding: 2px;">K</div> <p>INDUCTANCE TOLERANCE</p>
---	--	--	---



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.