## SanDisk<sup>®</sup> Waterproof USB Flash Drive

## The small, rugged and waterproof\* solution for emerging portable flash data storage applications.

As the need for storing, transporting and accessing critical medical records and other personal information continues to grow, SanDisk now offers a super-small, extremely hardy, waterproof USB flash drive to meet the increasing demands of the military, healthcare, emergency rescue and response, and other markets that need rugged, wearable storage.

The newest addition to the growing line of Hi-Speed USB 2.0 flash drives from SanDisk is small and stylish enough to be carried daily on a key chain or worn on a necklace, yet rugged and durable enough to withstand the harshest, most severe working environments of everyday life.

The SanDisk USB Flash Drive contains several safeguards against loss or damage. It is put through a special, low pressure overmolding process that seals the electronic components inside, making it waterproof. The SanDisk USB Flash Drive also features a specially designed, clear plastic cap that is always attached to the lanyard, assuring that the cap and lanyard remain securely fastened. Additionally, the cap features a unique latching mechanism that securely holds the USB drive in place and prevents accidental loss.

This USB Flash Drive is ideal for a wide range of emerging applications where small size, high durability, and ease of use are critical, including:

- Military: for storing soldiers' personal medical records and other personal information in the field, so that it can be easily read and written to in the field by ruggedized notebooks or PDAs equipped with a USB to PC Card adapter
- Healthcare: for storing personal health records so that it is readily available during an emergency
- Emergency Rescue & Response: for storing medical records for emergency rescue personnel (firefighters, police, paramedics, etc.)





## SanDisk Waterproof USB Flash Drive Preliminary Specifications\*\*

| Interface                      | Hi-Speed USB 2.0 (backwards compatible     |
|--------------------------------|--|
|                                | with all USB 1.1 ports)                    |
|                                | USB Mass Storage Class Device;             |
|                                | Certified Windows XP and Mac OS X          |
| Performance                    |  |
| Interface transfer speed (max) | Write: TBD                                 |
|                                | Read: TBD                                  |
| Power Requirements             |  |
| DC Input Voltage               | 4.6V to 5.4V                               |
| Environmental                  |  |
| Temperature                    |  |
| Operating Temperature          | 0°C to 45°C                                |
| Storage Temperature            | -45℃ to 85℃                                |
| Humidity                       |  |
| Operating                      | 8% to 95%, non-condensing                  |
| Non-operating                  | 8% to 95%, non-condensing                  |
| Physical Specifications        |  |
| Length                         | 55.7 mm                                    |
| Width                          | 19.0 mm                                    |
| Thickness                      | 7.8 mm                                     |
| Weight                         | 10.4 grams (11.5 grams w/cap)              |
| Сар                            | specially designed latching mechanism      |
|                                | and easy release                           |
| Ordering Information           |  |
| Model #                        | SDUSB-XXX-10Y-00 (Y: $1 = Blue, 2 = Red$ ) |
|                                | Where XXX= capacity: 32MB, 64MB, 128MB,    |
|                                | 256MB, 512MB, 1GB***                       |



\*Conforms to IEC 60529 IPX8 (to 4 feet/1.2 meters). Product must be clean and dry before use. \*\*Specifications and product offerings are subject to change without notice.

\*\*Specifications and product offerings are subject to change witho

\*\*\*\*1MB = 1 million bytes, 1GB = 1 billion bytes

SouthWest USA & Mexico 140 Caspian Court Sunnyvale, CA 94089 Phone: 760-736-8000

Eastern/North Central USA & Central/South America 134 Cherry Creek Circle Winter Springs, FL 32708 Phone: 407-366-6490 Fax: 407-366-5945 NorthEastern USA & Canada 620 Herndon Pkwy Suite 200 Herndon, VA 22070 Phone: 703-481-9828 Fax: 703-437-9215

Europe Netherlands Schipholpoort 40 2034 MB Haarlem, The Netherlands Phone: +31-23-551-4227 Fax: +31-23-532-5721 Central & Southern Europe Rudolf-Diesel-Str. 3 40822 Mettmann, Germany Phone: 49-210-495-3433 Fax: 49-210-495-3434

Korea #14-202, Anyang International Distribution Complex 555-9 Hogye-dong, Dongan-gu Anyang City, Kyounggi-Do 431 081

pe Japan

Nisso 15 Bldg. 8F 2-17-19 Shin-Yokohama, Kohoku-ku Yokohama 222-0033 Phone: 81-45-474-0181 Fax: 81-45-474-0371 Asia/Pacific Rim Suite 902-903 Bank of East Asia Harbour View Centre 56 Gloucester Road Wanchai Hong Kong Phone: 852-2712-0501 Fax: 852-2712-9385

140 Caspian Court • Sunnyvale, CA 94089 Phone: 408-542-0500 • Fax: 408-542-0503

For more information visit our web site at http://www.sandisk.com

SanDisk and the SanDisk Logo are trademarks of SanDisk Corporation, registered in the United States and other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). ©2005 SanDisk Corporation. All rights reserved. 80-11-00963 2/05