

Products

System Solutions

Support

Where to Buy

Press Room

Jobs

Site Index

Product Search

Advanced Search
Parametric Search

Home Optoelectronics Infrared Infrared

- Photocouplers
- •IrDA
- •IR Remote Receiver
- Photointerrupters
- Plastic Optical Fiber
- •Emitters Detectors
- Optical Systems

Resources

- •Discussion Forum
- Distributor Inventory
- Document Library
- •Lead Free
- PCNs and Errata

Location: Optoelectronics - Infrared » IR Remote Receiver » GP1UX517QS

GP1UX517QS

GP1UX51

Infrared Remote Control Receiver

Summary

Product Family

GP1UX51

Life Cycle Status

Production

Documentation



GP1UX517QS Information				
Application	Consumer Electronics, Audio/Visual equipment			
Detector position from PCB	6 mm			
Dissipation Current	1.5 Max mA			
Effective Range / Distance	5 meters minimum cm			
Features	Resin package with Plastic EMI shield, Lower height			
Number of Pins	3			
Operating Temperature	-10 to 70 °C			
Operating Voltage	4.5 to 5.5 V			
Package	Resin mold package with internal EMI shield			
Shipping Pack	Bags, 500 pieces			
Solder	Lead-Free			
Subcarrier Frequency	38 kHz			
View Orientation	Side			

GP1UX517QS Documentation					
DOCUMENT TYPE	FORMAT	SIZE	REVISION DATE		
Application Note - Key points for 100% utilization of optoelectronic devices. Chapters 2, 10 and 11 available. Other Chapters coming soon.	ndf	202.7K	04/15/2005		
Application Note - Use of IR Detecting Units For Remote Control	mage pdf	1402.2K	06/01/2005		
Application Note - Failure Analysis of Optoelectronic Devices	mage pdf	1487.5K			
Application Note - Use of Visible Light Emitting Diodes	mage pdf	1814.5K	04/15/2005		
Application Note - Use of Optical Fiber Links	mage pdf	1921.3K	04/15/2005		
Application Note - Use of IR Communication Devices Conforming to IrDA Standards	ndf	1206.8K	04/15/2005		

Specifications - GP1UX51QS Series - Infrared Detecting unit for Remote Control - PRODUCT SPECIFICATION - Spec No.: ED-03U020A	t pdf	317.9K	05/19/2004
Specifications - GP1UX51RK Series - Infrared Detecting unit for Remote Control - PRODUCT SPECIFICATION - Spec No.: ED-03U025	ndf	594.1K	12/27/2003
Technical Bulletin - Precaution for Photocouplers	mage pdf	78.6K	07/22/2003



Acrobat Adobe Acrobat Reader is needed to view our Product Documentation.

We also recommend downloading the Japanese Asian Font Pack.

Products | System Solutions | Support | Where to Buy | Press Room | Jobs | Site Index

Privacy Policy | Sales Terms | Limited Warranty | Important Restrictions | Contact Us | www.sharpsma.com The Sharp SMA website is maximized to perform best with Internet Explorer browser set to 800 X 600. © 2005 Sharp Electronics Corp.