

Product Search

Location: [Optoelectronics - Infrared](#) » [Plastic Optical Fiber](#) » GP1FD310TP

GP1FD310TP

[Advanced Search](#)[Parametric Search](#)

Home

Optoelectronics -

Infrared

Infrared

• [Photocouplers](#)• [IrDA](#)• [IR Remote Receiver](#)• [Photointerrupters](#)• [Plastic Optical Fiber](#)• [Emitters - Detectors](#)• [Optical Systems](#)

Resources

• [Discussion Forum](#)• [Distributor Inventory](#)• [Document Library](#)• [Lead Free](#)• [PCNs and Errata](#)

GP1FD310TP

Summary

Product Family

GP1FD310TP

Life Cycle Status

New



GP1FD310TP Information

Input Jack	ROUND
Transfer Rate	8 Mbit/s
Type	Transmitter
Vcc	3 to 3 V



Adobe Acrobat Reader is needed to view our Product Documentation.
 We also recommend downloading the [Japanese Asian Font Pack](#).

[Products](#) | [System Solutions](#) | [Support](#) | [Where to Buy](#) | [Press Room](#) | [Jobs](#) | [Site Index](#)

[Privacy Policy](#) | [Sales Terms](#) | [Limited Warranty](#) | [Important Restrictions](#) | [Contact Us](#) | [www.sharpsma.com](#)

The Sharp SMA website is maximized to perform best with Internet Explorer browser set to 800 X 600.

© 2005 Sharp Electronics Corp.

