

**Product Search**

 Location: [Optoelectronics - Infrared](#) » [Plastic Optical Fiber](#) » GP1FP513RK

# GP1FP513RK

[Advanced Search](#)
[Parametric Search](#)
**Home**
**Optoelectronics -**
**Infrared**
**Infrared**

- [Photocouplers](#)

- [IrDA](#)

- [IR Remote Receiver](#)

- [Photointerrupters](#)

- [Plastic Optical Fiber](#)

- [Emitters - Detectors](#)

- [Optical Systems](#)

**Resources**

- [Discussion Forum](#)

- [Distributor Inventory](#)

- [Document Library](#)

- [Lead Free](#)

- [PCNs and Errata](#)

**GP1FP513RK**
**Summary**
**Product Family**

GP1FP513RK

**Life Cycle Status**

New

**GP1FP513RK Information**

<b>Input Jack</b>	ComboJack
<b>Transfer Rate</b>	13.2 Mbit/s
<b>Type</b>	Receiver
<b>Vcc</b>	5 to 5 V



Adobe Acrobat Reader is needed to view our Product Documentation. We also recommend downloading the [Japanese Asian Font Pack](#).

[Products](#) | [System Solutions](#) | [Support](#) | [Where to Buy](#) | [Press Room](#) | [Jobs](#) | [Site Index](#)

[Privacy Policy](#) | [Sales Terms](#) | [Limited Warranty](#) | [Important Restrictions](#) | [Contact Us](#) | [www.sharpsma.com](#)

The Sharp SMA website is maximized to perform best with Internet Explorer browser set to 800 X 600.

© 2005 Sharp Electronics Corp.

