

66079

OPTICALLY COUPLED DIGITAL FILTER



11/11/03

Features:

- DSCC Approved 5962-916761HXX
- 10 MBd typical
- Meets Tempest EMI/RFI emanation criteria
- TTL compatible input and output
- RFI Rejection 80dB to 1GHz
- Faraday shield to provide high common mode rejection

Applications:


- Military and space
- Secure communication systems
- Isolated receiver input
- Microprocessor system interface
- Digital isolation for A/D, D/A converters

DESCRIPTION


The **66079** Optically Coupled Digital Filter consists of an LED optically coupled to a high speed, high gain inverting detector gate. Maximum isolation can be achieved while providing a TTL output capable of switching with propagation delays of 55ns typical. The 66079 is a hermetically sealed package which is threaded in order to provide convenient bulkhead mounting and is available in standard and screened versions or tested to customer specifications. The 66079-001 is a hermetically sealed package which can be soldered or press-fit mounted and is also available in standard and MIL-PRF-38534 screened versions or tested to customer specifications.

ABSOLUTE MAXIMUM RATINGS

Peak Forward Input Current (1ms duration)	40 mA
Forward Input Current Continuous	20 mA
Supply voltage (1 minute max)	7 V
Output Current	25 mA
Output Power Dissipation	40 mW
Output Voltage	7 V
Total Power Dissipation	350 mW
Storage Temperature	-65°C to +150°C
Operating Temperature	-55°C to +125°C
Lead Solder Temperature (10 second, 1/16" from case)	260°C

Package Dimensions

ALL DIMENSIONS ARE IN INCHES [MILLIMETERS]

Schematic Diagram

NOTE:
A 0.01 TO 0.1 μ F BYPASS CAPACITOR
MUST BE CONNECTED
BETWEEN VCC AND GND.

ELECTRICAL CHARACTERISTICS $T_A = -55^\circ\text{C}$ to $+125^\circ\text{C}$ unless otherwise specified.

PARAMETER	SYMBOL	MIN	Typ	MAX	UNITS	TEST CONDITIONS	NOTE
High Level Output Current	I_{OH}		5	250	μA	$V_{CC} = 5.5\text{V}$, $V_O = 5.5\text{V}$, $I_F = 250\mu\text{A}$	
Low Level Output Voltage	V_{OL}		0.5	0.6	V	$V_{CC} = 5.5\text{V}$, $I_F = 10\text{mA}$ I_{OL} (Sinking) = 10mA	3
High Level Supply Current	I_{CCH}		10	20	mA	$V_{CC} = 5.5\text{V}$, $I_F = 0$	
Low Level Supply Current	I_{CCL}		20	30	mA	$V_{CC} = 5.5\text{V}$, $I_F = 20\text{mA}$	
Input Forward Voltage	V_F		1.5	1.75	V	$I_F = 20\text{mA}$	
Input Reverse Breakdown Voltage	BV_R	5			V	$I_R = 10\mu\text{A}$	
Input-Output Insulation Leakage Current	I_{I-O}			1.0	μA	$V_{I-O} = 1000\text{Vdc}$, Relative Humidity = 45% $T_A = 25^\circ\text{C}$, $t = 5\text{s}$	
Propagation Delay Time To High Output Level	t_{PLH}		65	90	ns	$R_L = 510\Omega$, $C_L = 15\text{pF}$. $I_f = 13\text{mA}$, $T_A = 25^\circ\text{C}$	
Propagation Delay Time To Low Output Level	t_{PHL}		55	90	ns	$R_L = 510\Omega$, $C_L = 15\text{pF}$ $I_f = 13\text{mA}$, $T_A = 25^\circ\text{C}$	

TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, $V_{CC} = 5\text{V}$

PARAMETER	SYMBOL	MIN	Typ	MAX	UNITS	TEST CONDITIONS	NOTE
Input Capacitance	C_{IN}		60			$V_F = 0$, $f = \text{MHz}$	
Input to Case Capacitance	C_{IC}		2		pF	$V_F = 0$, $f = \text{MHz}$	
Input Diode Temperature Coefficient	$\frac{\Delta V_F}{\Delta T_A}$		-1.9		mV/°C	$I_F = 20\text{mA}$	
Capacitance (Input-Output)	C_{I-O}		1	3	pF	$f = 1\text{MHz}$	
Output Rise-Fall Time (10-90%)	t_f, t_f		35		ns	$R_L = 510\Omega$, $C_L = 50\text{pF}$ $I_f = 13\text{mA}$	
Common Mode Transient Immunity at High Output Level	CM_H	1000	10000		V/ μs	$V_{CM} = 50\text{V}$ (peak), V_O (min) = 2V, $R_L = 510\Omega$, $I_F = 0\text{mA}$	1
Common Mode Transient Immunity at Low Output Level	CM_L	1000	10000		V/ μs	$V_{CM} = 50\text{V}$ (peak), V_O (max) = 0.8V, $R_L = 510\Omega$, $I_F = 1\text{OmA}$	2

NOTES:

1. CM_H is the max. tolerable common mode transient to assure that the output will remain in a high logic state (i.e. $V_O > 2.0\text{V}$).
2. CM_L is the max. tolerable common mode transient to assure that the output will remain in a low logic state (i.e. $V_O < 0.8\text{V}$).
3. It is essential that a ceramic bypass capacitor of 0.01 μF to 0.1 μF be connected from VCC to GND.

RECOMMENDED OPERATING CONDITIONS:

PARAMETER	SYMBOL	MIN	MAX	UNITS
Input Current, Low Level Each Channel	I_{FL}	0	250	μA
Input Current, High Level Each Channel	I_{FH}	12.5	20	mA
Supply Voltage	V_C	4.5	5.5	V
Fan Out (TTL Load) Each Channel	N		6	
Operating Temperature	T_A	-55	125	°C

SELECTION GUIDE

PART NUMBER	PART DESCRIPTION
66079-000	DSCC Drawing # 5962-916761HXX , with housing
66079-001	DSCC Drawing #5962-916760HXX, without housing
66079-002	Commercial, mil-temp (-55°C to +125°C), with housing,
66079-003	Commercial, mil-temp (-55°C to +125°C), without housing
66079-004	Commercial, extended temp (-40°C to +80°C), without housing
66079-004H	Commercial, extended temp (-40°C to +80°C), with housing
66079-005	Commercial, temp (0°C to +70°C), without housing
66079-005H	Commercial, temp (0°C to +70°C), with housing