



Home > Products > Speed and Direction > SNDJ > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

SNDJ-H3L-G01



Zero speed hall sensor

Supporting Documentation

- ▶ [Installation Instructions](#)
- ▶ [Product Sheet](#)

| Product Specifications | |
|---------------------------|-----------------------------------|
| Sensing Type | Zero speed hall |
| Housing Diameter | 12 mm [0.47 in] |
| Barrel Length | 50 mm [1.97 in] |
| Vdc Supply | 8 Vdc to 25 Vdc |
| Operating Frequency Range | 0 Hz to 15 kHz |
| Operating Temperature | -20° to 100° C [-4 °F to 212 °F] |
| Connections | 1000 mm [39.4 in] leads |
| Availability | Global |
| UNSPSC Code | 411121 |
| UNSPSC Commodity | 411121 Transducers |
| Series Name | SNDJ |

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)