

Home > Products > Ultrasonic Sensors > 941-D > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

### 941-D4V-2D-1C0-180E



Actual product appearance may vary.

**Series 941 -D, Limit switch style, 2000 mm [79.0 in] scan distance, Connector M12, 5 pin, Analog 0 Vdc to 10 Vdc, teach in feature, IP67**

#### Features

Limit switch style sensor  
 Plastic Housing  
 Teach in  
 Sealing to IP67  
 M12 connector, 5 pin  
 Synchronizing/hold input: To avoid mutual interference from several sensors, they are very simply synchronised by connecting their synchronizing/hold input (pin 4) together. If the measure needs to be stopped, connect the synchronizing/hold input to the ground; the output stays stable.  
 Two switch point adjustment via teach in sequence  
 Temperature compensation

#### Potential Applications

Presence detection  
 Applications with restricted space  
 Slitter and rewinder machines  
 Cranes  
 Loop control

#### Description

The 941-D Series are industrial controls that perform distance measurement by using an ultrasonic beam. They provide all highend sensor features in a limit switch style housing. The sensor may be mounted in applications where space is a premium. Maximum scan range is 3,5 m [11.48 ft]. The 941-D comes with four output options; Analog (0 Vdc to 10 Vdc and 4 mA to 20 mA) and 2 PNP or 2 NPN switching outputs.

#### Supporting Documentation

- [Dimensions](#)
- [Installation Instructions Multiple Languages](#)
- [Electrical Connections](#)
- [Accessories: Standard or Angled Connector](#)
- [Accessory: Standard or Angled Connector with 2 m \[78.8 in\] Cable](#)

Product Specifications	
Sensing Range	200 mm to 2000 mm [8.0 in to 79.0 in]
Range Type	Middle range 1,0 m to 2,0 m [39.0 in to 79.0 in]
Min. Sensing Distance of Test Target	200 mm [8.0 in]
Supply Voltage	12 Vdc to 30 Vdc
Beam Angle	8°
Oscillating Frequency	180 KHz
Integrated Temperature Compensation	Yes
Repeatability	± 0.2 %, ± 2.0 mm [0.079 in]
Output Type	Analog 0 Vdc to 10 Vdc
Response Time	200 ms
Adjustment Method	Teach - in
Analog Output Slope Selection	Teach - in
Operating Temperature Range	-15 °C to 70 °C [5 °F to 158 °F]
Storage Temperature	-25 °C to 70 °C [ - 13 °F to 158 °F]
Linearity	< 0.5 %
Indicators	4 LED
Additional Inputs/Outputs	Hold/Synchronisation
Memory	EEPROM (non - volatile)
Current Consumption	< 45 mA
Circuit Protection	Reverse Polarity, voltage spikes on supply and output lines, short circuit on switching output
Housing Style	Limit Switch style
Housing Material	Polyethyleneterephthalat
Sealing	IP67
Mounting	3 holes
Sensing Face Material	Epoxy
Termination Type	Connector
Connector Type	M12, 5 pin (female connector not included)
Availability	Global
Normally Open/Normally Closed selection	Teach - in
UNSPSC Code	41111926
UNSPSC Commodity	41111926 Proximity sensors
Series Name	941 -D

#### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

#### Keyword Search

Search for product and support information.

All Sensing and Control

#### Product Search

Part number search:

Use (\*) to expand search

[Specification Search](#)