

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

941-D4V-2D-1C0-130E



Actual product appearance may vary.

Series 941 -D, Limit switch style, 3500 mm [138.0 in] scan distance, Connector M12, 5 pin, Analog 0 Vdc to 10 Vdc, teach in feature, IP67

Features

Limit switch style sensor
 Plastic Housing
 Teach in
 Sealing to IP67
 M12 connector, 5 pin
 Synchronizing/hold input: To avoid mutual interference from several sensors, they are very simply synchronised by connecting their synchronizing/hold input (pin 4) together. If the measure needs to be stopped, connect the synchronizing/hold input to the ground; the output stays stable.
 Two switch point adjustment via teach in sequence
 Temperature compensation

Potential Applications

Presence detection
 Applications with restricted space
 Slitter and rewinder machines
 Cranes
 Loop control

Description

The 941-D Series are industrial controls that perform distance measurement by using an ultrasonic beam. They provide all highend sensor features in a limit switch style housing. The sensor may be mounted in applications where space is a premium. Maximum scan range is 3,5 m [11.48 ft]. The 941-D comes with four output options; Analog (0 Vdc to 10 Vdc and 4 mA to 20 mA) and 2 PNP or 2 NPN switching outputs.

Supporting Documentation

- ▣ [Dimensions](#)
- ▣ [Installation Instructions Multiple Languages](#)
- ▣ [Electrical Connections](#)
- ▣ [Accessories: Standard or Angled Connector](#)
- ▣ [Accessory: Standard or Angled Connector with 2 m \[78.8 in\] Cable](#)

Product Specifications	
Sensing Range	300 mm to 3500 mm [12.0 in to 138.0 in]
Range Type	Long range > 2.0 m [80.0 in] and up
Min. Sensing Distance of Test Target	300 mm [12.0 in]
Supply Voltage	12 Vdc to 30 Vdc
Beam Angle	8°
Oscillating Frequency	130 KHz
Integrated Temperature Compensation	Yes
Repeatability	± 0.2 %, ± 2.0 mm [0.079 in]
Output Type	Analog 0 Vdc to 10 Vdc
Response Time	400 ms
Adjustment Method	Teach - in
Analog Output Slope Selection	Teach - in
Operating Temperature Range	-15 °C to 70 °C [5 °F to 158 °F]
Storage Temperature	-25 °C to 70 °C [- 13 °F to 158 °F]
Linearity	< 0.5 %
Indicators	4 LED
Additional Inputs/Outputs	Hold/Synchronisation
Memory	EEPROM (non - volatile)
Current Consumption	< 45 mA
Circuit Protection	Reverse Polarity, voltage spikes on supply and output lines, short circuit on switching output
Housing Style	Limit Switch style
Housing Material	Polyethyleneterephthalat
Sealing	IP67
Mounting	3 holes
Sensing Face Material	Epoxy
Termination Type	Connector
Connector Type	M12, 5 pin (female connector not included)
Availability	Global
Normally Open/Normally Closed selection	Teach - in
UNSPSC Code	41111926
UNSPSC Commodity	41111926 Proximity sensors
Series Name	941 -D

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)