



Home > Products > Piezoresistive Silicon > XCXL > Product Page

Order Product and Get Support

- ▣ U.S. Authorized Distributors
- ▣ Global Sales & Service
- ▣ N. American Sales Reps
- ▣ Distributor Inventory
- ▣ Technical Assistance
- ▣ White Papers
- ▣ Literature Request
- ▣ Test and Measurement Catalog
- ▣ RoHS Product List
- ▣ Customer Feedback

XCXL004DNC



Actual product appearance may vary.

Pressure Sensors: Measurement Type: Differential, Gage, Vacuum Gage; Signal Conditioning: Unamplified; Pressure Range: ± 4.0 inches of water; Port Style: Barbed: Commercial Grade

Features

Pressure Ranges from 4 in H₂O, 10 in H₂O 1 psi through 150 psi
 Calibrated offset to ±mV
 Calibrated Full Scale Span to ±1.0 % FS over Compensated Temperature Range
 Temperature Compensated over 0? C to +70 ? C
 Gage, Differential, and Absolute Pressure
 Burst Pressure 3X Rated
 Ratiometric mV Output

Potential Applications

Medical Applications
 Applications Requiring Small Size
 Applications Requiring Vacuum, Positive Pressure or Both

Description

The XCXL, XCX Series integrates silicon micromachined sensing technology, temperature compensation, and calibration in an improved performance industry standard package. A unique stress isolating design protects against torque induced errors typically found in competitive products. Additional stability and long term accuracy improvements are gained through simplified compensation techniques, which eliminate temperature dependent thermal compensation. This series is available in a commercial (XCXDNC) performance level. This performance level provides the calibration accuracy of offset thermal compensation, and linearity providing added flexibility to meet critical performance budgets. The XCA and XCR Series provide amplified output as well as integrated compensation.

Supporting Documentation

[▣ Dimensions](#)

[▣ Equivalent Circuit, Pin Designations](#)

[▣ Engineering Drawing](#)

Product Specifications	
Measurement Type	Differential, Vacuum Gage, Gage
Signal Conditioning	Unamplified
Pressure Range	± 4.0 in H ₂ O
Maximum Overpressure	5.0 psi
Supply Voltage	3.0 Vdc min., 12.0 Vdc typ., 16.0 Vdc max.
Compensated	Yes
Output Calibration	Yes
Termination	PCB
Port Style	Barbed
Package Style	Honeywell DI - XCX
Typical Sensitivity	10 mV/in H ₂ O
Full Scale Span	40 mV typ.
Null Offset	0 mV typ.
Null Shift over Temperature	± 1 mV
Span Shift Over Temperature	± 2% span
Linearity, Hysteresis Error	± 0.5 % Span Typ.; ± 1 % Span Max.
Repeatability	0.1% span typ.
Input Resistance	15.0 kOhm
Shock	10 g
Weight	7.6 g [0.27 oz]
Operating Temperature Range	-25 °C to 85 °C [-13 °F to 185 °F]
Compensated Temperature Range	0 °C to 50 °C [32 °F to 122 °F]
Storage Temperature Range	-40 °C to 125 °C [-40 °F to 257 °F]
Media Compatibility	Port 1: Dry gases only. Media must be compatible with epoxy based adhesive. Port 2: Wetted materials. Media must be compatible with nylon housing, epoxy adhesive and silicon.
UNSPSC Code	411121
UNSPSC Commodity	411121 Transducers
Availability	Global
Series Name	XCXL

My Links

Login to iCOM
 Login as Rep/AD
 Login as Guest
 Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search