


- Sensors
- Proximity Sensors
 - Cylindrical
 - E2EH
 - E2E
 - E2V-X[]
 - E2EM
 - E2EQ
 - E2FM
 - E2FQ
 - E2EZ
 - E2F
 - E2EY
 - E2EV
 - E2E2**
 - E2A
 - Rectangular
 - Separate Amplifier
 - Capacitive
 - Others
 - Accessories

- Sensors
- Switches
- Safety Components
- Relays
- Control Components
- Automation Systems
- Motion & Drives
- In Addition
- Cautions
- Applications
- Item A to Z Index

E2E2-X2C1 5M

Inquiry of E2E2-X2C1 5M



*3D-CAD CG View

Products links

Find OMRON IA Products in your country

Similar items

- E2E2X2C1-M1
- E2E2X2C2 2M
- E2E2X2C2-M1
- Item index of E2E2

- Ratings / Performance**
- Dimensions
- Output circuit diagram
- Timing chart
- Sensing range

- Sensing distance vs. size and material of sensing
- Mutual interference
- Effects of surrounding metals

For print

Shield	Shielded
Cylinder type sensing head size	M12
Sensing method	Inductive type
Sensing distance	2 mm-10% to +10%
Setting distance	0 to 1.6 mm
Differential distance	10% Max. of sensing distance
Sensing object	Ferrous metal (Sensitivity lowers with non-ferrous metals.)
Standard sensing object	Iron 12*12*1mm
Response frequency	DC: 1.5 kHz (average)
Power supply voltage	12 to 24 VDC (ripple(pp) :10% Max.)
Operating voltage range	10 to 55 VDC
Current consumption	13 mA Max.
Control output (Output type)	NPN open collector output
Control output (Switching capacity)	0 to 200 mA (55VDC Max.)
Control output (Residual voltage)	(DC) 2 V Max. (under load current with cable length of 2m)
Indicator	Operation indicator(red)
Operation mode	NO
Protective circuit	Surge suppressor Output short-cut protection Power supply reverse polarity protection
Standard or Different frequency	Standard
Ambient temperature	Operating: -40 to 85 CEL Storage: -40 to 85 CEL (with no icing or condensation)
Ambient humidity	Operating: 35 to 95 %RH Storage: 35 to 95 %RH (with no condensation)
Temperature influence	+10% Max. of sensing distance in temperature range of -25 to +70CEL +15% Max. of sensing distance in temperature range of -40 to +85CEL (As the basis for sensing distance of 23CEL)
Voltage influence	+1% Max. of sensing distance in rated voltage range +15%. (As the basis for sensing distance at standard power voltage)
Insulation resistance	50 M OHM Min. at 500VDC between charged parts and the case
Dielectric strength	1000 VAC 50/60 Hz for 1 minute between charged parts and the case
Vibration resistance	10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y, and Z directions
Shock resistance	1000m/s2 for 10 times each in X, Y, and Z directions
Degree of protection	IEC60529: IP67 Company standard: OIproof
Applicable standard (EC Directive (Low Voltage Directive))	EN60947-1 EN60947-2
Applicable standard (EC Directive (EMC Directive))	EMI: EN60947-2 Emission Enclosure: CISPR11 Group classA EMS: EN60947-2 Immunity ESD: IEC61000-2 Immunity RF-interference: IEC61000-4-3 Immunity Burst: IEC61000-4 CE marking: Equipped
Applicable standard (CCC mark)	Not equipped
Connection method	Pre-wired models (Cable length: 5 m)
Material (case)	Brass nickel plating
Material (sensing surface)	PBT
Material (clamping nuts)	Brass nickel plating
Material (toothed washer)	Iron zinc plating
Accessories	Instruction manual

As of June 3, 2008

[Top of page](#)