


NOT RECOMMENDED FOR NEW DESIGNS,
PLEASE USE GBU6005 - GBU610

Features

- UL Recognized, File #94661
- Ideal for Printed Circuit Board
- Surge Overload Rating of 250A Peak
- Low Forward Voltage Drop
- The Plastic Material Carries UL Recognition 94V-0
- **Lead Free Finish, RoHS Compliant (Date Code 0514+)**
(Note 2)

Mechanical Data

- Case: RS-6, Molded Plastic
- Terminals: Leads Solderable per MIL-STD-202, Method 208
- Polarity: Symbols Marked on Body
- Approx. Weight: 8.0 grams



RS-6		
Dim	Min	Max
A	22.7	23.7
B	3.6	4.1
C	4.2	4.7
D	1.7	2.2
E	10.3	11.3
G	4.5	6.8
H	4.6	5.6
J	25.4	-
K	-	19.3
L	16.8	17.8
M	6.6	7.1
N	4.7	5.2
P	1.2	1.3
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics @ T_A = 25°C unless otherwise specified

Single phase, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	RS 601	RS 602	RS 603	RS 604	RS 605	RS 606	RS 607	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	V _{RSM}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current @ T _C = 100°C @ T _A = 40°C	I _(AV)	6.0							A
Peak Forward Surge current, 8.3 ms half sine-wave superimposed on rated load	I _{FSM}	250							A
Maximum DC Forward Voltage Drop per element at 3.0A	V _F	1.0							V
Maximum DC Reverse Current at Rated DC Blocking Voltage, per element @ T _A = 25°C @ T _A = 100°C	I _R	10 1.0							μA mA
Maximum Thermal Resistance (Note 1)	R _{JC}	4.7							°C/W
Operating Temperature Range	T _J	-55 to +125							°C
Storage Temperature Range	T _{STG}	-55 to +150							°C

- Notes:
1. Thermal Resistance junction to case per diode.
 2. EC Directive 2002/95/EC (RoHS) revision 13.2.2003. Glass and High Temperature Solder Exemptions Applied, see *EU Directive Annex Notes 5 and 7*.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Typical Reverse Characteristics




Fig. 4 Max Non-Repetitive Peak Forward Surge Current




Fig. 5 Typical Junction Capacitance Per Element

Ordering Information (Note 3)

Device	Packaging	Shipping
RS601	RS-6	0.5K Bulk
RS602	RS-6	0.5K Bulk
RS603	RS-6	0.5K Bulk
RS604	RS-6	0.5K Bulk
RS605	RS-6	0.5K Bulk
RS606	RS-6	0.5K Bulk
RS607	RS-6	0.5K Bulk

Notes: 3. For packaging details, visit our website at <http://www.diodes.com/datasheets/ap2008.pdf>

IMPORTANT NOTICE

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

The products located on our website at www.diodes.com are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the expressed written approval of Diodes Incorporated.