



Single Phase Rectifier Bridge

 $I_{dAV} = 21 \text{ A}$
 $V_{RRM} = 800-1800 \text{ V}$

V_{RSM} V	V_{RRM} V	Type
900	800	VBO 22-08NO8
1300	1200	VBO 22-12NO8
1700	1600	VBO 22-16NO8
1900	1800	VBO 22-18NO8



N

Symbol	Conditions	Maximum Ratings		
I_{dAV}	$T_C = 85^\circ\text{C}$, module	17	A	
I_{dAVM}	$T_C = 63^\circ\text{C}$, module	21	A	
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$; $t = 10 \text{ ms}$ (50 Hz) $V_R = 0$ $t = 8.3 \text{ ms}$ (60 Hz)	380	A	
		440	A	
	$T_{VJ} = T_{VJM}$; $t = 10 \text{ ms}$ (50 Hz) $V_R = 0$ $t = 8.3 \text{ ms}$ (60 Hz)	360	A	
		400	A	
I^2t	$T_{VJ} = 45^\circ\text{C}$; $t = 10 \text{ ms}$ (50 Hz) $V_R = 0$ $t = 8.3 \text{ ms}$ (60 Hz)	725	A^2s	
		800	A^2s	
	$T_{VJ} = T_{VJM}$; $t = 10 \text{ ms}$ (50 Hz) $V_R = 0$ $t = 8.3 \text{ ms}$ (60 Hz)	650	A^2s	
		650	A^2s	
T_{VJ}		-40...+150	$^\circ\text{C}$	
T_{VJM}		150	$^\circ\text{C}$	
T_{stg}		-40...+150	$^\circ\text{C}$	
V_{ISOL}	50/60 Hz, RMS $t = 1 \text{ min}$ $I_{ISOL} \leq 1 \text{ mA}$ $t = 1 \text{ s}$	2500	V~	
		3000	V~	
M_d	Mounting torque (M5) (10-32 UNF)	2 $\pm 10\%$ 18 $\pm 10\%$	Nm lb.in.	
Weight	Typ.	22	g	
Symbol	Conditions	Characteristic Values		
I_R	$V_R = V_{RRM}$ $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = T_{VJM}$	0.3 5.0	mA	
V_F	$I_F = 150 \text{ A}$ $T_{VJ} = 25^\circ\text{C}$	2.2	V	
V_{TO}	For power-loss calculations only	0.85	V	
r_t		12	$\text{m}\Omega$	
R_{thJC}	per diode; 120° el. per module	8.20 2.05	K/W	
R_{thJH}	per diode; 120° el. per module	9.40 2.35	K/W	
d_s	Creeping distance on surface	12.7	mm	
d_A	Creepage distance in air	9.4	mm	
a	Max. allowable acceleration	50	m/s^2	

Data according to IEC 60747 and refer to a single diode unless otherwise stated.

IXYS reserves the right to change limits, test conditions and dimensions.

© IXYS All rights reserved

Features

- Package with 1/4" fast-on terminals
- Isolation voltage 3000 V~
- Planar passivated chips
- Blocking voltage up to 1800 V
- Low forward voltage drop
- UL registered E 72873


Applications

- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Advantages

- Easy to mount with one screw
- Space and weight savings
- Improved temperature & power cycling

Dimensions in mm (1 mm = 0.0394")






Fig. 1 Forward current versus voltage drop per diode




Fig. 2 Surge overload current per diode
 I_{FSM} : Crest value. t: duration




Fig. 3 I^2t versus time (1-10 ms)
per diode or thyristor




Fig. 4 Power dissipation vs. direct output current and ambient temperature




Fig. 5 Maximum forward current
at case temperature




Fig. 6 Transient thermal impedance per diode or thyristor, calculated

IXYS reserves the right to change limits, test conditions and dimensions.

20100706c

© IXYS All rights reserved

2 - 2