

# Silicon Carbide Schottky Rectifier Bridge



in ISOPLUS i4-PAC™

## FBS 16-06SC

$$V_{RRM} = 600 \text{ V}$$

$$I_{D(AV)M} = 11 \text{ A}$$

$$C_{junction} = 21 \text{ pF}$$



### Rectifier Bridge

Symbol	Conditions	Maximum Ratings	
$V_{RRM}$		600	V
$I_{FAV}$	$T_C = 90^\circ\text{C}$ ; sine $180^\circ$ (per diode)	5	A
$I_{D(AV)M}$	$T_C = 90^\circ\text{C}$	11	A
$I_{FSM}$	$T_{VJ} = 25^\circ\text{C}$ ; $t = 10 \text{ ms}$ ; sine 50 Hz	20	A
$P_{tot}$	$T_C = 25^\circ\text{C}$ (per diode)	27	W

Symbol	Conditions	Characteristic Values ( $T_{VJ} = 25^\circ\text{C}$ , unless otherwise specified)		
		min.	typ.	max.
$V_F$	$I_F = 6 \text{ A}$ ; $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		1.5 1.6	V V
$I_R$	$V_R = V_{RRM}$ ; $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		0.05	0.2 mA mA
$C_J$	$V_R = 400 \text{ V}$ ; $T_{VJ} = 125^\circ\text{C}$		21	pF
$R_{thJC}$ $R_{thJS}$	(per diode)		8.6	5.6 K/W K/W

### Features

- Silicon Carbide Schottky Diodes
  - no reverse recovery at turn off - only charge of junction capacity - soft turn off waveform
  - no forward recovery at turn on
  - switching behaviour independent of temperature
  - low leakage current
- ISOPLUS i4-PAC(TM) package
  - isolated back surface
  - low coupling capacity between pins and heatsink
  - enlarged creepage towards heatsink
  - application friendly pinout
  - high reliability
  - industry standard outline

### Applications

- output rectifiers of high end switched mode power supplies
- other high frequency rectifiers

Data according to IEC 60747 and refer to a single diode unless otherwise stated.

### Component

Symbol	Conditions	Maximum Ratings	
$T_{VJ}$		-55...+175	°C
$T_{stg}$		-55...+125	°C
$V_{ISOL}$	$I_{ISOL} \leq 1 \text{ mA}; 50/60 \text{ Hz}$	2500	V~
$F_C$	mounting force with clip	20...120	N

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
$C_p$	coupling capacity between shorted pins and mounting tab in the case		40	pF
$d_{S^1d_A}$	pin - pin	1.7		mm
$d_{S^1d_A}$	pin - backside metal	5.5		mm
<b>Weight</b>			9	g

### Dimensions in mm (1 mm = 0.0394")

