

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311


Phone: (818) 701-4933 Fax: (818) 701-4939

BAV99BRW


Features

- Low Current Leakage
- Low Cost
- Small Outline Surface Mount Package
- Lead Free Finish/Rohs Compliant ("P"Suffix designates RoHS Compliant. See ordering information)
 AC
 C
 C

MAKING:KGJ



Moisture Sensitivity Level 1




Maximum Ratings

- Operating Temperature: -65°C to +150°C
- Storage Temperature: -65°C to +150°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Reverse Voltage	V_R	75V	
Average Rectified	lo	150mA	
Output Current			
Power Dissipation	P _{TOT}	200mW	
Maximum Instantaneous Forward Voltage	V_{F}	715mV 855mV 1000mV 1250mV	I _{FM} = 1mA; I _{FM} = 10mA; I _{FM} = 50mA; I _{FM} = 150mA;
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	2.5uA 0.025uA	VR=75V VR=20V
Typical Junction Capacitance	CJ	2.0pF	Measured at 1.0MHz, V _R =0V
Reverse Recovery Time	T _{rr}	4nS	$I_F=I_R=10$ mA $I_{rr}=0.1*I_R$ $R_c=100\Omega$

200mW 75Volt Plastic-Encapsulate Diode





DIMENSIONS							
	INCHES		ММ				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.006	.014	0.15	0.35			
В	.045	.053	1.15	1.35			
С	.085	.096	2.15	2.45			
D	.026		0.65Nominal				
G	.047	.055	1.20	1.40			
Н	.071	.087	1.80	2.20			
J		.004		0.10			
K	.035	.043	0.90	1.10			
L	.010	.018	0.26	0.46			
M	003	006	0.08	0.15			




Typical Characteristics

BAV99BRW







 T_A , AMBIENT TEMPERATURE (°C) Fig. 4 Power Derating Curve, Note 1



Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.