

Schottky

High Performance Schottky Diode
Low Loss and Soft Recovery
Common Cathode



$$V_{RRM} = 60 \text{ V}$$

$$I_{FAV} = 2 \times 30 \text{ A}$$

$$V_F = 0.67 \text{ V}$$

Part number (Marking on product)

DSB 60 C 60HB



Features / Advantages:

- Very low V_f
- Extremely low switching losses
- Low I_{rm} -values
- Improved thermal behaviour
- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Low losses

Applications:

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

Package:

TO-247AD


- Industry standard outline
- Epoxy meets UL 94V-0
- RoHS compliant

| Symbol | Definition | Conditions | Ratings | | | Unit |
|------------|-------------------------------------|---|---------|------|------|------------------|
| | | | min. | typ. | max. | |
| V_{RRM} | max. repetitive reverse voltage | $T_{VJ} = 25 \text{ }^\circ\text{C}$ | | | 60 | V |
| I_R | reverse current | $V_R = 60 \text{ V}$ | | | 20 | mA |
| | | $V_R = 60 \text{ V}$ | | | 50 | mA |
| V_F | forward voltage | $I_F = 30 \text{ A}$ | | | 0.77 | V |
| | | $I_F = 60 \text{ A}$ | | | 1.18 | V |
| | | $I_F = 30 \text{ A}$ | | | 0.67 | V |
| | | $I_F = 60 \text{ A}$ | | | 0.92 | V |
| I_{FAV} | average forward current | rectangular, $d = 0.5$ | | | 30 | A |
| V_{FO} | threshold voltage | for power loss calculation only | | | 0.46 | V |
| r_F | slope resistance | | | | 6.2 | m Ω |
| R_{thJC} | thermal resistance junction to case | | | | 0.95 | K/W |
| T_{VJ} | virtual junction temperature | | -55 | | 150 | $^\circ\text{C}$ |
| P_{tot} | total power dissipation | $T_C = 25 \text{ }^\circ\text{C}$ | | | 130 | W |
| I_{FSM} | max. forward surge current | $t_p = 10 \text{ ms (50 Hz), sine}$ | | | 320 | A |
| C_J | junction capacitance | $V_R = \text{ V; } f = 1 \text{ MHz}$ | | | | pF |
| E_{AS} | non-repetitive avalanche energy | $I_{AS} = \text{ A; } L = 100 \text{ } \mu\text{H}$ | | | tbd | mJ |
| I_{AR} | repetitive avalanche current | $V_A = 1.5 \cdot V_R$ typ.; $f = 10 \text{ kHz}$ | | | tbd | A |

| Symbol | Definition | Conditions | Ratings | | | Unit |
|---------------|-------------------------------------|------------|---------|------|------|------|
| | | | min. | typ. | max. | |
| I_{RMS} | RMS current | per pin* | | | 50 | A |
| R_{thCH} | thermal resistance case to heatsink | | | 0.25 | | K/W |
| M_D | mounting torque | | 0.8 | | 1.2 | Nm |
| F_C | mounting force with clip | | 20 | | 120 | N |
| T_{stg} | storage temperature | | -55 | | 150 | °C |
| Weight | | | | 6 | | g |

* Irms is typically limited by: 1. pin-to-chip resistance; or by 2. current capability of the chip.

In case of 1, a common cathode/anode configuration and a non-isolated backside, the whole current capability can be used by connecting the backside.

Outlines TO-247AD


| Dim. | Millimeter | | Inches | |
|------|------------|-------|--------|-------|
| | Min. | Max. | Min. | Max. |
| A | 19.81 | 20.32 | 0.780 | 0.800 |
| B | 20.80 | 21.46 | 0.819 | 0.845 |
| C | 15.75 | 16.26 | 0.610 | 0.640 |
| D | 3.55 | 3.65 | 0.140 | 0.144 |
| E | 4.32 | 5.49 | 0.170 | 0.216 |
| F | 5.4 | 6.2 | 0.212 | 0.244 |
| G | 1.65 | 2.13 | 0.065 | 0.084 |
| H | - | 4.5 | - | 0.177 |
| J | 1.0 | 1.4 | 0.040 | 0.055 |
| K | 10.8 | 11.0 | 0.426 | 0.433 |
| L | 4.7 | 5.3 | 0.185 | 0.209 |
| M | 0.4 | 0.8 | 0.016 | 0.031 |
| N | 1.5 | 2.49 | 0.087 | 0.102 |