

ECS-CR2-B

SMD CERAMIC RESONATOR

The ECS-CR2-B Chip Type SMD ceramic resonator includes built in capacitors for reduced component count. The SMD Ceramic resonator is an excellent low cost frequency control solution when absolute frequency accuracy is not important.

OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS

PART NUMBER *	FREQUENCY RANGE (MHz)	FREQUENCY ACCURACY @ 25°C (%)	FREQUENCY STABILITY -20 ~ +80°C (%)	AGING FOR TEN YEARS (%)	ESR (Ω) MAX.	BUILT-IN CAPACITANCE (C1 & C2)	INSULATION RESISTANCE @ 10VDC
ECS-CR2-DD.DD-B	8.00 ~ 13.00	± 0.5	± 0.3	± 0.3	25	30 pF	100 M Ω Min.
ECS-CR2-DD.DD-B	13.10 ~ 40.00	± 0.5	± 0.3	± 0.3	40	15 pF	100 M Ω Min.

Complete part number to include frequency i.e. ECS-CR2-20.00-B-TR

PACKAGE DIMENSIONS (mm)

TIONAL





Figure 1) ECS-CR2-B Series - Top and Side Views



PIN CONNECTIONS				
#1	In/Out			
#2	Ground			
#3	Out/In			




Figure 2) Test Circuit (74HCU04P)




Figure 3) Land Pattern

DIMENSIONS (mm)					
T1	T2	Т3	W1		
0.7 ± 0.2	1.0±0.2	1.5±0.2	4.1±0.2		

PART NUMBERING GUIDE: "Example" ECS-CR2-20.00-B-TR ECS - Series - Frequency - Version - Packaging CR2 = 8 ~ 13 MHz CR2 = 13.1 ~ 40 MHz CR2 = 13.1 ~ 40 MHz CR2 = 13.1 ~ 40 MHz



May 16, 2007

ECS, Inc. International 1105 South Ridgeview Road Olathe, KANSAS, 66062 USA www.ecsxtal.com 913-782-7787 1-800-237-1041 Fax: 913-782-6991

Mike Huennekens Director of Marketing and OEM Sales E-mail: mikeh@ecsxtal.com Phone: 1-800-237-1041

CERAMIC RESONATOR/FILTER

Application Information Request

Attention: All Customers

From: Mike Huennekens, Director of Marketing and OEM Sales

Subject: Ceramic Resonator Application Information Request

ECS is requesting that you complete the section below that will allow us to determine if the specific application is suitable for the ceramic resonator/filters that you have requested.

Ceramic Resonators/Filters, both surface mount and through-hole type, are a much different frequency control solution than that of a crystal based device. Not only are there "matching" issues to specific integrated circuits and processors with ceramic based piezoelectric components but for multiple reasons ceramics are not the most advantageous nor robust frequency control solution for certain applications.

In addition, ECS does not approve the use of its ceramic products in Automotive, Military, Avionics, Life Sustaining or Life Support systems or any other related medical application.

If the customer chooses to use this product in one or more of the noted applications without the written consent of ECS, Inc., ECS, Inc. shall be held harmless, and given release of liability and indemnification from claims of any nature.

Please complete the following and submit this form as soon as possible.

ECS Part Number	
Estimated Annual Usage	
Has this part already been approved for this application?	Yes No
Has this part been ordered previously for this application?	Yes No
End Customer	
Application Details You Must Be Specific or this may be returned for more information.	

I certify that the above information is true and correct to the best of my knowledge and acknowledge that ECS will be held harmless if this item is used in the restricted applications noted above.

Company Name

Print Your Name

Title

Signature

Date

** If this item will be used by a 3rd party ECS may require a form be completed and signed by all parties.

To be completed by ECS Inc., International					
Approved:	Disallowed:	Date:	Approved By:		

Please direct any further inquires to Brad Slatten at <u>brads@ecsxtal.com</u> or Carla Williams at <u>carlaw@ecsxtal.com</u>. We thank you for your understanding and patience in this process.