

# International Rectifier

- RoHs Compliant and Halogen Free ①
- Low Profile (<0.7 mm)
- Dual Sided Cooling Compatible ①
- Ultra Low Package Inductance
- Optimized for High Frequency Switching ①
- Ideal for CPU Core DC-DC Converters
- Optimized for Sync. FET socket of Sync. Buck Converter ①
- Low Conduction and Switching Losses
- Compatible with existing Surface Mount Techniques ①
- 100% R<sub>g</sub> tested


## IRF6724MPbF

## IRF6724MTRPbF

DirectFET™ Power MOSFET ②

Typical values (unless otherwise specified)

V <sub>DSS</sub>	V <sub>GS</sub>	R <sub>DS(on)</sub>	R <sub>DS(on)</sub>		
30V max	±20V max	1.9mΩ@ 10V	2.7mΩ@ 4.5V		
Q <sub>g tot</sub>	Q <sub>gd</sub>	Q <sub>gs2</sub>	Q <sub>rr</sub>	Q <sub>oss</sub>	V <sub>gs(th)</sub>
33nC	10nC	3.9nC	34nC	20nC	1.8V



Applicable DirectFET Outline and Substrate Outline (see p.7,8 for details) ①

SQ	SX	ST	MQ	MX	MT	MP			
----	----	----	----	----	----	----	--	--	--

### Description

The IRF6724MPbF combines the latest HEXFET® Power MOSFET Silicon technology with the advanced DirectFET™ packaging to achieve the lowest on-state resistance in a package that has the footprint of a SO-8 and only 0.7 mm profile. The DirectFET package is compatible with existing layout geometries used in power applications, PCB assembly equipment and vapor phase, infra-red or convection soldering techniques, when application note AN-1035 is followed regarding the manufacturing methods and processes. The DirectFET package allows dual sided cooling to maximize thermal transfer in power systems, improving previous best thermal resistance by 80%.

The IRF6724MPbF balances both low resistance and low charge along with ultra low package inductance to reduce both conduction and switching losses. The reduced total losses make this product ideal for high efficiency DC-DC converters that power the latest generation of processors operating at higher frequencies. The IRF6724MPbF has been optimized for parameters that are critical in synchronous buck including R<sub>ds(on)</sub>, gate charge and C<sub>dV/dt</sub>-induced turn on immunity. The IRF6724MPbF offers particularly low R<sub>ds(on)</sub> and high C<sub>dV/dt</sub> immunity for synchronous FET applications.

### Absolute Maximum Ratings

	Parameter	Max.	Units
V <sub>DS</sub>	Drain-to-Source Voltage	30	V
V <sub>GS</sub>	Gate-to-Source Voltage	±20	
I <sub>D</sub> @ T <sub>A</sub> = 25°C	Continuous Drain Current, V <sub>GS</sub> @ 10V ③	27	
I <sub>D</sub> @ T <sub>A</sub> = 70°C	Continuous Drain Current, V <sub>GS</sub> @ 10V ③	21	A
I <sub>D</sub> @ T <sub>C</sub> = 25°C	Continuous Drain Current, V <sub>GS</sub> @ 10V ④	150	
I <sub>DM</sub>	Pulsed Drain Current ⑤	212	
E <sub>AS</sub>	Single Pulse Avalanche Energy ⑥	12	mJ
I <sub>AR</sub>	Avalanche Current ⑤	21	A




Fig 1. Typical On-Resistance Vs. Gate Voltage

Notes:

- ① Click on this section to link to the appropriate technical paper.
- ② Click on this section to link to the DirectFET Website.
- ③ Surface mounted on 1 in. square Cu board, steady state.

[www.irf.com](http://www.irf.com)





Fig 2. Typical Total Gate Charge vs Gate-to-Source Voltage

- ④ T<sub>C</sub> measured with thermocouple mounted to top (Drain) of part.
- ⑤ Repetitive rating; pulse width limited by max. junction temperature.
- ⑥ Starting T<sub>J</sub> = 25°C, L = 0.051mH, R<sub>G</sub> = 25Ω, I<sub>AS</sub> = 21A.

Static @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$BV_{DSS}$	Drain-to-Source Breakdown Voltage	30	—	—	V	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	22	—	mV/ $^\circ\text{C}$	Reference to $25^\circ\text{C}, I_D = 1\text{mA}$
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	—	1.90	2.50	$\text{m}\Omega$	$V_{GS} = 10\text{V}, I_D = 27\text{A}$ ⑦
		—	2.70	3.50		$V_{GS} = 4.5\text{V}, I_D = 21\text{A}$ ⑦
$V_{GS(th)}$	Gate Threshold Voltage	1.35	1.8	2.35	V	$V_{DS} = V_{GS}, I_D = 100\mu\text{A}$
$\Delta V_{GS(th)}/\Delta T_J$	Gate Threshold Voltage Coefficient	—	-6.1	—	mV/ $^\circ\text{C}$	
$I_{DSS}$	Drain-to-Source Leakage Current	—	—	1.0	$\mu\text{A}$	$V_{DS} = 24\text{V}, V_{GS} = 0\text{V}$
		—	—	150		$V_{DS} = 24\text{V}, V_{GS} = 0\text{V}, T_J = 125^\circ\text{C}$
$I_{GSS}$	Gate-to-Source Forward Leakage	—	—	100	nA	$V_{GS} = 20\text{V}$
	Gate-to-Source Reverse Leakage	—	—	-100		$V_{GS} = -20\text{V}$
$g_{fs}$	Forward Transconductance	130	—	—	S	$V_{DS} = 15\text{V}, I_D = 21\text{A}$
$Q_g$	Total Gate Charge	—	33	54	nC	$V_{DS} = 15\text{V}$ $V_{GS} = 4.5\text{V}$ $I_D = 21\text{A}$ See Fig. 15
$Q_{gs1}$	Pre-V <sub>th</sub> Gate-to-Source Charge	—	8.5	—		
$Q_{gs2}$	Post-V <sub>th</sub> Gate-to-Source Charge	—	3.9	—		
$Q_{gd}$	Gate-to-Drain Charge	—	10	—		
$Q_{godr}$	Gate Charge Overdrive	—	11	—		
$Q_{sw}$	Switch Charge ( $Q_{gs2} + Q_{gd}$ )	—	14	—	pF	$V_{DS} = 16\text{V}, V_{GS} = 0\text{V}$
$Q_{oss}$	Output Charge	—	20	—		
$R_G$	Gate Resistance	—	1.2	2.2		
$t_{d(on)}$	Turn-On Delay Time	—	11	—		
$t_r$	Rise Time	—	19	—	ns	$V_{DD} = 15\text{V}, V_{GS} = 4.5\text{V}$ ⑦ $I_D = 21\text{A}$ $R_G = 1.8\Omega$
$t_{d(off)}$	Turn-Off Delay Time	—	23	—		
$t_f$	Fall Time	—	16	—		
$C_{iss}$	Input Capacitance	—	4404	—	pF	$V_{GS} = 0\text{V}$ $V_{DS} = 15\text{V}$ $f = 1.0\text{MHz}$
$C_{oss}$	Output Capacitance	—	885	—		
$C_{rss}$	Reverse Transfer Capacitance	—	424	—		

## Diode Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
$I_S$	Continuous Source Current (Body Diode)	—	—	150	A	MOSFET symbol showing the integral reverse p-n junction diode. 
$I_{SM}$	Pulsed Source Current (Body Diode) ⑤	—	—	212		
$V_{SD}$	Diode Forward Voltage	—	—	1.0	V	$T_J = 25^\circ\text{C}, I_S = 21\text{A}, V_{GS} = 0\text{V}$ ⑦
$t_{rr}$	Reverse Recovery Time	—	20	30	ns	$T_J = 25^\circ\text{C}, I_F = 21\text{A}$ $dI/dt = 300\text{A}/\mu\text{s}$ ⑦
$Q_{rr}$	Reverse Recovery Charge	—	34	51	nC	

## Notes:

- ⑤ Repetitive rating; pulse width limited by max. junction temperature.  
 ⑦ Pulse width  $\leq 400\mu\text{s}$ ; duty cycle  $\leq 2\%$ .

### Absolute Maximum Ratings

	Parameter	Max.	Units
P <sub>D</sub> @ T <sub>A</sub> = 25°C	Power Dissipation ③	2.8	W
P <sub>D</sub> @ T <sub>A</sub> = 70°C	Power Dissipation ③	1.8	
P <sub>D</sub> @ T <sub>C</sub> = 25°C	Power Dissipation ④	89	
T <sub>P</sub>	Peak Soldering Temperature	270	°C
T <sub>J</sub>	Operating Junction and Storage Temperature Range	-40 to + 150	
T <sub>STG</sub>			

### Thermal Resistance

	Parameter	Typ.	Max.	Units
R <sub>0JA</sub>	Junction-to-Ambient ③⑩	—	45	
R <sub>0JA</sub>	Junction-to-Ambient ⑧⑩	12.5	—	
R <sub>0JA</sub>	Junction-to-Ambient ⑨⑩	20	—	°C/W
R <sub>0JC</sub>	Junction-to-Case ④⑩	—	1.4	
R <sub>0J-PCB</sub>	Junction-to-PCB Mounted	1.0	—	
	Linear Derating Factor ③	0.022		W/°C





Fig 3. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient ①


#### Notes:

- ⑧ Used double sided cooling, mounting pad with large heatsink.
- ⑨ Mounted on minimum footprint full size board with metalized back and with small clip heatsink.


⑩ R<sub>θ</sub> is measured at T<sub>j</sub> of approximately 90°C.



③ Surface mounted on 1 in. square Cu (still air).




⑨ Mounted to a PCB with small clip heatsink (still air)




⑩ Mounted on minimum footprint full size board with metalized back and with small clip heatsink (still air)

# IRF6724MPbF


International  
Rectifier




**Fig 4.** Typical Output Characteristics




**Fig 5.** Typical Output Characteristics




**Fig 6.** Typical Transfer Characteristics




**Fig 7.** Normalized On-Resistance vs. Temperature




**Fig 8.** Typical Capacitance vs. Drain-to-Source Voltage




**Fig 9.** Typical On-Resistance Vs. Drain Current and Gate Voltage




**Fig 10.** Typical Source-Drain Diode Forward Voltage




**Fig 11.** Maximum Safe Operating Area




**Fig 12.** Maximum Drain Current vs. Case Temperature




**Fig 13.** Typical Threshold Voltage vs. Junction Temperature




**Fig 14.** Maximum Avalanche Energy Vs. Drain Current




**Fig 15a.** Gate Charge Test Circuit




**Fig 15b.** Gate Charge Waveform




**Fig 16a.** Unclamped Inductive Test Circuit




**Fig 16b.** Unclamped Inductive Waveforms



**Fig 17a.** Switching Time Test Circuit



**Fig 17b.** Switching Time Waveforms




**Fig 18.** Diode Reverse Recovery Test Circuit for N-Channel HEXFET® Power MOSFETs

### DirectFET™ Board Footprint, MX Outline (Medium Size Can, X-Designation).


Please see DirectFET application note AN-1035 for all details regarding the assembly of DirectFET.

This includes all recommendations for stencil and substrate designs.




## DirectFET™ Outline Dimension, MX Outline (Medium Size Can, X-Designation).


Please see AN-1035 for DirectFET assembly details and stencil and substrate design recommendations



## DirectFET™ Part Marking




## DirectFET™ Tape & Reel Dimension (Showing component orientation).



NOTE: Controlling dimensions in mm  
Std reel quantity is 4800 parts. (ordered as IRF6724MTRPbF). For 1000 parts on 7" reel, order IRF6724MTR1PbF

REEL DIMENSIONS								
STANDARD OPTION (QTY 4800)				TR1 OPTION (QTY 1000)				
CODE	METRIC	MIN	MAX	IMPERIAL	METRIC	MIN	MAX	
A	330.0	N.C.	12.992	N.C.	177.77	N.C.	6.9	N.C.
B	20.2	N.C.	0.795	N.C.	19.06	N.C.	0.75	N.C.
C	12.8	13.2	0.504	0.520	13.5	12.8	0.53	0.50
D	1.5	N.C.	0.059	N.C.	1.5	N.C.	0.059	N.C.
E	100.0	N.C.	3.937	N.C.	58.72	N.C.	2.31	N.C.
F	N.C.	18.4	N.C.	0.724	N.C.	13.50	N.C.	0.53
G	12.4	14.4	0.488	0.567	11.9	12.01	0.47	N.C.
H	11.9	15.4	0.469	0.606	11.9	12.01	0.47	N.C.

### LOADED TAPE FEED DIRECTION



NOTE: CONTROLLING  
DIMENSIONS IN MM

DIMENSIONS				
	METRIC		IMPERIAL	
CODE	MIN	MAX	MIN	MAX
A	7.90	8.10	0.311	0.319
B	3.90	4.10	0.154	0.161
C	11.90	12.30	0.469	0.484
D	5.45	5.55	0.215	0.219
E	5.10	5.30	0.201	0.209
F	6.50	6.70	0.256	0.264
G	1.50	N.C.	0.059	N.C.
H	1.50	1.60	0.059	0.063

Data and specifications subject to change without notice.  
This product has been designed and qualified for the Consumer market.  
Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.04/2009