
SMD ONE PORT 433.92 MHz SAW RESONATOR

ASR433.92E





> STANDARD SPECIFICATIONS:

CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.
Center Frequency Fo		MHz	433.845	433.920	433.995	
Tolerance from Fo		KHz		±75		
Insertion Loss			dB	-	1.3	2.0
Quality Factor	Unloaded		-		10,500	
	50 Ω loaded				1,450	
Temperature Stability	Turnover Temperature		°C	25	40	55
	Turnover Frequency		KHz		Fc	
	Freq. Temp. Coefficient		ppm/°C ²		0.037	
Frequency Aging			ppm/year		±10	
DC Insulation Resistance			MΩ	1.0		
RF Equivalent RLC Model	Motional Resistance R ₁		Ω		16	26
	Motional Inductance L ₁		μH		61.724	
	Motional Capacitance C ₁		fF		2.1817	
	Shunt Capacitance C ₀		pF	1.9	2.2	2.5
Operating temp.		°C	-40°C to +85°C			
Storage temp.		°C	-45°C to +85°C			
Max. Rating	DC voltage	C voltage V ±10				
RF Power Dissipation		dBm	10			

Data measured with: Source Impedance: $Zs=50\Omega$, Load Impedance: $ZL=50\Omega$, TA=25°C Electrostatic Sensitive Device. Handle with precaution.


▷ MARKING:

- 433.92
- AR ZYX
- from A to L; Y for year, I.e. 4 for 2004 X: Traceability code)


(433.92 Frequency in MHz)

(ZY: Date code Z for month

PIN NO.	CONNECTIONS		
2	Input/Output		
6	Output/Input		
4 & 8	Case Ground		
1,3,5,7	N/C		







ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

CORPORATION

Downloaded from Elcodis.com electronic components distribut